

Digital Video Recorder

User Manual

Legal Information

About this Document

- This Document includes instructions for using and managing the Product. Pictures, charts, images and all other information hereinafter are for description and explanation only.
- The information contained in the Document is subject to change, without notice, due to firmware updates or other reasons. Please find the latest version of the Document at the Hikvision website (<u>https://www.hikvision.com</u>). Unless otherwise agreed, Hangzhou Hikvision Digital Technology Co., Ltd. or its affiliates (hereinafter referred to as "Hikvision") makes no warranties, express or implied.
- Please use the Document with the guidance and assistance of professionals trained in supporting the Product.

About this Product

- This product can only enjoy the after-sales service support in the country or region where the purchase is made.
- If the product you choose is a video product, please scan the following QR code to obtain the "Initiatives on the Use of Video Products", and read it carefully.



Acknowledgment of Intellectual Property Rights

- Hikvision owns the copyrights and/or patents related to the technology embodied in the Products described in this Document, which may include licenses obtained from third parties.
- Any part of the Document, including text, pictures, graphics, etc., belongs to Hikvision. No part of this Document may be excerpted, copied, translated, or modified in whole or in part by any means without written permission.
- **HIKVISION** and other Hikvision's trademarks and logos are the properties of Hikvision in various jurisdictions.
- Other trademarks and logos mentioned are the properties of their respective owners.
- **HDMI** The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries.

LEGAL DISCLAIMER

• TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THIS DOCUMENT AND THE PRODUCT DESCRIBED, WITH ITS HARDWARE, SOFTWARE AND FIRMWARE, ARE PROVIDED "AS IS" AND "WITH ALL FAULTS AND ERRORS". HIKVISION MAKES NO WARRANTIES, EXPRESS OR

IMPLIED, INCLUDING WITHOUT LIMITATION, MERCHANTABILITY, SATISFACTORY QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. THE USE OF THE PRODUCT BY YOU IS AT YOUR OWN RISK. IN NO EVENT WILL HIKVISION BE LIABLE TO YOU FOR ANY SPECIAL, CONSEQUENTIAL, INCIDENTAL, OR INDIRECT DAMAGES, INCLUDING, AMONG OTHERS, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, OR LOSS OF DATA, CORRUPTION OF SYSTEMS, OR LOSS OF DOCUMENTATION, WHETHER BASED ON BREACH OF CONTRACT, TORT (INCLUDING NEGLIGENCE), PRODUCT LIABILITY, OR OTHERWISE, IN CONNECTION WITH THE USE OF THE PRODUCT, EVEN IF HIKVISION HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR LOSS.

- YOU ACKNOWLEDGE THAT THE NATURE OF THE INTERNET PROVIDES FOR INHERENT SECURITY RISKS, AND HIKVISION SHALL NOT TAKE ANY RESPONSIBILITIES FOR ABNORMAL OPERATION, PRIVACY LEAKAGE OR OTHER DAMAGES RESULTING FROM CYBER-ATTACK, HACKER ATTACK, VIRUS INFECTION, OR OTHER INTERNET SECURITY RISKS; HOWEVER, HIKVISION WILL PROVIDE TIMELY TECHNICAL SUPPORT IF REQUIRED.
- YOU AGREE TO USE THIS PRODUCT IN COMPLIANCE WITH ALL APPLICABLE LAWS, AND YOU ARE SOLELY RESPONSIBLE FOR ENSURING THAT YOUR USE CONFORMS TO THE APPLICABLE LAW. ESPECIALLY, YOU ARE RESPONSIBLE, FOR USING THIS PRODUCT IN A MANNER THAT DOES NOT INFRINGE ON THE RIGHTS OF THIRD PARTIES, INCLUDING WITHOUT LIMITATION, RIGHTS OF PUBLICITY, INTELLECTUAL PROPERTY RIGHTS, OR DATA PROTECTION AND OTHER PRIVACY RIGHTS. YOU SHALL NOT USE THIS PRODUCT FOR ANY PROHIBITED END-USES, INCLUDING THE DEVELOPMENT OR PRODUCTION OF WEAPONS OF MASS DESTRUCTION, THE DEVELOPMENT OR PRODUCTION OF CHEMICAL OR BIOLOGICAL WEAPONS, ANY ACTIVITIES IN THE CONTEXT RELATED TO ANY NUCLEAR EXPLOSIVE OR UNSAFE NUCLEAR FUEL-CYCLE, OR IN SUPPORT OF HUMAN RIGHTS ABUSES.
- IN THE EVENT OF ANY CONFLICTS BETWEEN THIS DOCUMENT AND THE APPLICABLE LAW, THE LATTER PREVAILS.

© Hangzhou Hikvision Digital Technology Co., Ltd. All rights reserved.

Regulatory Information

FCC Information

Please take attention that changes or modification not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. FCC compliance: This equipment has been tested and found to comply with the limits for pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Conditions

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.

EU Conformity Statement



This product and - if applicable - the supplied accessories too are marked with "CE" and comply therefore with the applicable harmonized European standards listed under the EMC Directive 2014/30/EU, LVD Directive 2014/35/EU, the RoHS Directive 2011/65/EU.



2012/19/EU (WEEE directive): Products marked with this symbol cannot be disposed of as unsorted municipal waste in the European Union. For proper recycling, return this product to your local supplier upon the purchase of equivalent new equipment, or dispose of it at designated collection points. For more information see: <u>http://www.recyclethis.info</u>.



Regulation (EU) 2023/1542(Battery Regulation): This product contains a battery and it is in conformity with the Regulation (EU) 2023/1542. The battery cannot be disposed of as unsorted municipal waste in the European Union. See the product documentation for specific battery information. The battery is marked with this symbol, which may include lettering to indicate cadmium (Cd), or lead (Pb). For proper recycling, return the battery to your supplier or to a designated collection point. For more information see: www.recyclethis.info

Applicable Model

This manual is applicable to the following models.

Series	Model
iDS-7200HUHI-M1/E	iDS-7208HUHI-M1/E
	iDS-7204HUHI-M1/PXT
	iDS-7208HUHI-M2/PXT
	iDS-7216HUHI-M2/PXT
iDS-7100HUHI-M1/S (E)	iDS-7108HUHI-M1/S (E)
	iDS-7204HUHI-M1/X
iDS-7200HUHI-M1/E iDS-7200HUHI-M/PXT iDS-7100HUHI-M1/S (E) iDS-7200HUHI-M1/X iDS-7200HUHI-M2/X iDS-7100HQHI-M1/S (E) iDS-7200HQHI-M1/E iDS-7200HQHI-M1/XT	iDS-7208HUHI-M1/X
	iDS-7204HUHI-M2/X
	iDS-7216HUHI-M2/X
	iDS-7208HUHI-M2/X
iDS-7100HQHI-M1/S (E)	iDS-7116HQHI-M1/S (E)
iDS-7200HQHI-M1/E	iDS-7216HQHI-M1/E
	iDS-7204HQHI-M1/XT
iDS-7200HQHI-M1/XT	iDS-7208HQHI-M1/XT
iDS-7200HQHI-M1/E iDS-7200HQHI-M1/XT	iDS-7216HQHI-M1/XT
	iDS-7208HQHI-M2/XT
iDS-7200HQHI-M2/XT	iDS-7216HQHI-M2/XT
	iDS-7232HQHI-M2/XT
	iDS-7204HTHI-M1/XT
iDS-7208HTHI-M2/XT	iDS-7204HTHI-M2/XT
	iDS-7208HTHI-M2/XT

Symbol Conventions

The symbols that may be found in this document are defined as follows.

Symbol	Description
Danger	Indicates a hazardous situation which, if not avoided, will or could result in death or serious injury.
Caution	Indicates a potentially hazardous situation which, if not avoided, could result in equipment damage, data loss, performance degradation, or unexpected results.
i Note	Provides additional information to emphasize or supplement important points of the main text.

Safety Instruction

- Proper configuration of all passwords and other security settings is the responsibility of the installer and/or end-user.
- In the use of the product, you must be in strict compliance with the electrical safety regulations of the nation and region.
- Firmly connect the plug to the power socket. Do not connect several devices to one power adapter. Power off the device before connecting and disconnecting accessories and peripherals.
- Shock hazard! Disconnect all power sources before maintenance.
- The equipment must be connected to an earthed mains socket-outlet.
- The socket-outlet shall be installed near the device and shall be easily accessible.
- For the device with the sign 4 indicating hazardous live, the external wiring connected to the terminals requires installation by an instructed person.
- Never place the device in an unstable location. The device may fall, causing serious personal injury or death.
- Input voltage should meet the SELV (Safety Extra Low Voltage) and the LPS (Limited Power Source) according to the IEC62368.
- High touch current! Connect to earth before connecting to the power supply.
- If smoke, odor or noise rise from the device, turn off the power at once and unplug the power cable, and then please contact the service center.
- Use the device in conjunction with an UPS, and use factory recommended HDD if possible.
- This equipment is not suitable for use in locations where children are likely to be present.
- CAUTION: Risk of explosion if the battery is replaced by an incorrect type.
- Do not ingest battery. Chemical Burn Hazard!
- This product contains a coin/button cell battery. If the coin/button cell battery is swallowed, it can cause severe internal burns in just 2 hours and can lead to death.
- Improper replacement of the battery with an incorrect type may defeat a safeguard (for example, in the case of some lithium battery types).
- Do not dispose of the battery into fire or a hot oven, or mechanically crush or cut the battery, which may result in an explosion.
- Do not leave the battery in an extremely high temperature surrounding environment, which may result in an explosion or the leakage of flammable liquid or gas.
- Do not subject the battery to extremely low air pressure, which may result in an explosion or the leakage of flammable liquid or gas.
- Dispose of used batteries according to the instructions.
- Keep body parts away from fan blades and motors. Disconnect the power source during servicing.
- Keep body parts away from motors. Disconnect the power source during servicing.
- Use only power supplies same with the original model, or LPS power supplies with the same voltage and electric current.
- In order to prevent data leakage, please use the Secure Erase function to clear data before discarding your SSD device.

Preventive and Cautionary Tips

Before connecting and operating your device, please be advised of the following tips:

- The device is designed for indoor use only. Install it in a well-ventilated, dust-free environment without liquids.
- Ensure recorder is properly secured to a rack or shelf. Major shocks or jolts to the recorder as a result of dropping it may cause damage to the sensitive electronics within the recorder.
- The device shall not be exposed to water dripping or splashing, and no objects filled with liquids, such as vases, shall be placed on the device.
- No naked flame sources, such as lighted candles, should be placed on the device.
- The ventilation should not be impeded by covering the ventilation openings with items, such as newspapers, table-cloths, curtains, etc. The openings shall never be blocked by placing the equipment on a bed, sofa, rug or other similar surface.
- For certain models, ensure correct wiring of the terminals for connection to an AC mains supply.
- For certain models, the equipment has been designed, when required, modified for connection to an IT power distribution system.
- **±** identifies the battery holder itself and identifies the positioning of the cell(s) inside the battery holder.
- + identifies the positive terminal(s) of equipment which is used with, or generates direct current. identifies the negative terminal(s) of equipment which is used with, or generates direct current.
- If the device has been powered off or placed for a long time, its coin/button cell battery may run out power.
- When the coin/button cell battery runs out power, the system time would be incorrect, please contact the after-sales service to replace the battery.
- Keep a minimum 200 mm (7.87 inch) distance around the equipment for sufficient ventilation.
- For certain models, ensure correct wiring of the terminals for connection to an AC mains supply.
- Do not touch the sharp edges or corners.
- When the device is running above 45 °C (113 °F), or its HDD temperature in S.M.A.R.T. exceeds the stated value, please ensure the device is running in a cool environment, or replace HDD(s) to make the HDD temperature in S.M.A.R.T. below the stated value.
- Provide a surge suppressor at the inlet opening of the device under special conditions such as the mountain top, iron tower, and forest.
- Do not touch the bare components (such as the metal contacts of the inlets) and wait for at least 5 minutes, since electricity may still exist after the device is powered off.
- The USB port of the equipment is used for connecting to a mouse, keyboard, USB flash drive, or Wi-Fi dongle only. The current for the connected device shall be not more than 0.1 A.
- The serial port of the device is used for debugging only.
- If the power output port of the device does not comply with Limited Power Source, the connected device powered by this port shall be equipped with a fire enclosure.
- If a power adapter is provided in the device package, use the provided adapter only.
- For the device with sticker 🛕 or 🛲, pay attention to the following cautions: CAUTION: Hot

parts! Do not touch. Burned fingers when handling the parts. Wait one-half hour after switching off before handling the parts.

- If the device needs to be installed on the wall or ceiling, install the device according to the instructions in this manual.
- To prevent injury, this device must be securely attached to the installation surface in accordance with the installation instructions.
- Under high working temperature (40 °C (104 °F) to 55 °C (131 °F)), the power of some power adapters may decrease. Make sure that the power has been disconnected before you wire, install, or disassemble the device.
- If the device needs to be wired by yourself, select the corresponding wire to supply power according to the electric parameters labeled on the device. Strip off wire with a standard wire stripper at corresponding position. To avoid serious consequences, the length of stripped wire shall be appropriate, and conductors shall not be exposed.
- If smoke, odor, or noise arises from the device, immediately turn off the power, unplug the power cable, and contact the service center.

Indicator and Interface Description


Interface Description

The panel interfaces vary with different models. Refer to the following table for common interface description.

ltem	Description
VIDEO IN	BNC interface for Turbo HD and analog video input.
VIDEO OUT	BNC connector for video output.
AUDIO IN	RCA connector for audio input.
AUDIO OUT	RCA connector for audio output.
LINE IN	RCA connector for two-way audio input.
USB	Universal Serial Bus (USB) interface for additional device.
VGA	DB15 connector for local video output and menu display.
HDMI	HDMI interface for video output.
RS-485	RS-485 serial interface for pan/tilt unit, speed dome, etc.
RS-232	RS-232 interface for parameter configuration, or transparent channel.
LAN	RJ-45 self-adaptive Ethernet interface.
eSATA	Storage and expansion interface for record or backup.
GND	Ground.
Power Switch	Switch for turning on/off the device.
Power Supply	100 to 240 VAC, 48 VDC, or 12 VDC power supply.
USIM Card	UIM/SIM card slot.
Ψ	SMA antenna interface.
ALARM IN	The alarm input receives alarm input signal. The equipment positive terminal (+) should connect to a number, and the equipment negative terminal (-) should connect to "-" or "G".
	Use the following diagram as a connection example for alarm input.

Table 1-2 Common	Indicator Description
------------------	-----------------------

ALARM OUT Image: Constrained and the connect to a number with "A", and its negative Image: Constrained and the connect to a number with "A", and its negative Image: Constrained and the connect to a number with "A", and its negative Image: Constrained and the connect to a number with "A", and its negative Image: Constrained and the connect to a number with "A", and its negative to the connect to the corresponding number with "B", and then connect to "" or "G". Use the following diagram as an alarm output connection example for DC equipment. Image: Constrained and the connect to the connect to "" or "G". Use the following diagram as an alarm output connection example for DC equipment. Image: Constrained and the connect to the connect to "" or "G". Use the following diagram as an alarm output connection example for DC equipment. Image: Constrained and the connect to the con	ltem	Description
ALARM OUT Image: Construction of the second sec		ALARM OUT RS-485
ALARM OUT When an equipment uses DC power supply, its positive terminal (+) should both connect to the corresponding number with "B", and then connect to "-" or "G". Use the following diagram as an alarm output connection example for DC equipment. ALARM OUT Image: Comparison of the corresponding in the connect to the corresponding number with "B", and then connect to "-" or "G". Use the following diagram as an alarm output connection example for DC equipment. ALARM OUT Image: Comparison of the corresponding in the connect to the corresponding in the connect in		
ALARM OUT Image: Connect to a number with "A", and its negative terminal (-) should both connect to the corresponding number with "B", and then connect to "-" or "G". Use the following diagram as an alarm output connection example for DC equipment. ALARM OUT Image: Connect to a number with "A", and its negative terminal (-) should both connect to "-" or "G". Use the following diagram as an alarm output connection example for DC equipment. Image: Connect to a number with "A", and its negative terminal (-) should connect to a number with "A", and its negative		The alarm output sends out alarm signal.
ALARM OUT ALARM IN + Equipment positive terminal (+) should connect to a number with "A", and its negative		connect to a number with "A", and its negative terminal (-) should both connect to the corresponding number with "B", and then connect to "-" or "G". Use the following diagram as an alarm output connection example for DC equipment.
Use the following diagram as an alarm output connection example for AC	ALARM OUT	ALARM OUT RS-485 We is the image of



ltem	Description
	5A 5B 6A 6B 7A 7B 8A 8B 9A 9B ALARM OUT RS-485 1A 1B 2A 2B 3A 3B 4A 4B T+T-R+R2
	A+ Equipment B-
	Controllable 12 VDC and 0.5/1 A power output for external alarm device. The power will be turned on when the corresponding alarm output is triggered.
	Use the following diagram for reference.
	5A 5B 6A 6B 7A 7B 8A 8B 9A 9B ALARM OUT RS-485 1A 1B 2A 2B 3A 3B4A 4B 14 T= R+R=
Ctrl 12V/ ^{12V}	
	+ Equipment
	It provides 12 VDC and 1 A power output.
	Use the following diagram for reference.
	5A 5B 6A 6B 7A 7B 8A 8B 9A 9B ALARM OUT RS-485 12V=1 12 A 2B 3A 3B 4A 4B T+T-R+R= + +
DC 12V/ ^{12V}	
	+ Equipment

HDD Installation

If your device does not support HDD hot swapping, disconnect the power from the device before installing a hard disk drive (HDD). A factory recommended HDD should be used for this installation. Scan the QR code below to view HDD installation videos.



• Figure 1-1 HDD Installation

Bracket Installation

Bracket installation is applicable when it requires to remove the device cover, and install HDD on the internal bracket.

Steps

1. Unfasten screws on the back, and push the cover backwards to remove the cover.



Figure 1-2 Remove Cover

2. Fix the HDD on the bracket with screws.

iNote

Please uninstall the upper layer bracket first before installing HDD on the lower layer bracket.




Figure 1-3 Fix HDD

3. Connect the data cable and power cable.




Figure 1-4 Connect Cable

iNote

You can repeat the steps above to install other HDDs.

4. Reinstall the device cover and fasten screws.

Front Panel Plug-Pull Installation

Front panel plug-pull installation is applicable when you need to open the device front panel with

key and install the HDD.

Steps

1. Fix mounting ears to HDD with screws.




Figure 1-5 Fix Mounting Ears to HDD

2. Unlock the front panel with the attached key, and press the buttons on both sides of the front panel to open it.




Figure 1-6 Open Front Panel

3. Insert the HDD until it is fixed firmly.




Figure 1-7 Insert HDD

- 4. Optional: Repeat the steps above to install other HDDs.
- 5. Close the front panel and lock it with key.

HDD Case Installation

HDD case installation refers to the method that you install the HDD in the case, and then plug the HDD case into the slot.

Steps

- 1. Unlock the front panel with panel key.
- 2. Pull the front panel out of the device and make it a little above the left handle.

iNote

The angle between the front panel and the device must be within 10°.

3. Press the blue button to pop up the handle and hold the handle and pull the HDD case out of the slot.

4. Fix the hard disk in the HDD case.

- 1) Place a HDD in the case. The SATA interface must face the case bottom.
- 2) Adjust the HDD position. Ensure the hard disk rear aligns with HDD bottom.
- 3) Use a screwdriver to fasten the four screws into the screw holes in both sides.




Figure 1-8 Fix HDD

5. Push the HDD case back into the slot.




Figure 1-9 Push HDD Case into Slot

6. Press the handle until you hear a click. Thus to fix the HDD case. Repeat above steps to install the rest hard disk boxes.

7. Close the front panel, and lock it with the panel key.

Fix-on-Bottom Installation

Fix-on-bottom installation is applicable when you need to install and fix the HDD on the device bottom.

Steps

1. Remove the cover from device by unfastening the screws on panels.




Figure 1-10 Remove Cover

- 2. Connect the data cable and power cable.
- 1) Connect one end of data cable to the device motherboard.
- 2) Connect the other end of data cable to HDD.
- 3) Connect one end of power cable to HDD.
- 4) Connect the other end of power cable to the device motherboard.




Figure 1-11 Connect Cables

3. Set the device up, match HDD screw threads with the reserved holes on the device bottom, and fix HDD with screws.




Figure 1-12 Fix HDD to Device Bottom

- 4. Optional: Repeat the steps above to install other HDDs.
- 5. Reinstall the device cover and fasten screws.

Coin/Button Cell Battery Replacement

The coin/button cell battery should be replaced when the device has been powered off or placed for a long time, and the system time is incorrect.

Before You Start

Power off your device.

Steps

- 1. Remove the device chassis cover.
- 2. Find the coin/button cell battery on motherboard.

3. Put the thumb outside the battery slot, and use the index finger to push the positive contact spring outward gently. The battery will pop up automatically.




Figure 1-1 Remove Battery

iNote

You should wear anti-static gloves when removing the battery.

If the spring is deformed due to excessive force when pushing outward, it needs to be adjusted back into its original position before inserting the battery.

4. Insert the battery diagonally towards the side with the plastic snap point in the battery slot, and then press the battery near the positive contact spring to snap it beneath the spring.




Figure 1-2 Replace Battery

iNote

You should wear anti-static gloves when replacing the battery.

5. Reinstall the device chassis cover.

What to do next

If the system time is incorrect, please go to configure the time.

Contents

Chapter 1 Startup1
1.1 Activate Your Device
1.2 Login
1.2.1 Log in via Unlock Pattern
1.2.2 Log in via Password
Chapter 2 Live View
2.1 GUI Introduction
2.1.1 Customize Window Division
2.2 PTZ Control
2.2.1 Configure PTZ Parameter7
2.2.2 PTZ Control Panel Introduction8
2.2.3 Customize Preset
2.2.4 Customize Patrol8
2.2.5 Customize Pattern
Chapter 3 Playback
3.1 GUI Introduction
3.2 Normal Playback11
3.3 Event Playback
3.4 Slice Playback 14
3.5 Back up Clip 15
Chapter 4 Search File
4.1 Search Human by Face Picture
4.2 Quick Backup
Chapter 5 Configuration (Easy Mode)20
5.1 System Configuration20
5.1.1 General
5.1.2 User
5.1.3 Exception
5.2 Network Configuration

5.2.1 General
5.2.2 Hik-Connect
5.2.3 Email
5.3 Camera
5.3.1 Network Camera27
5.3.2 OSD Settings
5.3.3 Motion Detection
5.4 Configure Alarm Linkage Action
5.5 Configure Arming Schedule
5.6 Recording Management
5.6.1 Storage Device
5.6.2 Configure Recording Schedule
5.6.3 Configure Recording Parameter
Chapter 6 Configuration (Expert Mode)37
6.1 System Configuration
6.1.1 General
6.1.2 Live View
6.1.3 User
6.2 Network Configuration40
6.2.1 General
6.2.2 Platform Access
6.2.3 Email
6.3 Camera Management
6.3.1 Configure Signal Input
6.3.2 Network Camera
6.3.3 Display Settings
6.3.4 Privacy Mask
6.4 Event Configuration
6.4.1 Multi-Capability Intelligence
6.4.2 Normal Event61
6.4.3 Perimeter Protection

6.4.4 Face Recognition	
6.4.5 Configure Arming Schedu	le73
6.4.6 Configure Alarm Linkage	Action
6.5 Intelligent Search	
6.5.1 AcuSearch	
6.6 Recording Management	
6.6.1 Configure Recording Sche	dule
6.6.2 Configure Recording Para	meter
6.6.3 Storage Device	
6.6.4 Configure Storage Mode	
6.6.5 Advanced Settings	
6.7 Face Picture Library Manageme	nt
6.7.1 Add a Face Picture Librar	/
6.7.2 Upload Face Pictures to t	he Library84
Chapter 7 Maintenance	
7.1 Restore Default	
7.2 Search Log	
7.3 System Service	
7.4 Buzzer Switch	
7.5 Device Maintenance	
7.5.1 Schedule Reboot	
7.5.2 Device Status	
7.5.3 Time Sync Diagnosis	
7.6 Upgrade	
7.6.1 Local Upgrade	
7.6.2 Online Upgrade	
Chapter 8 Alarm	
8.1 Set Event Hint	
8.2 View Alarm in Alarm Center	
Chapter 9 Web Operation	
9.1 Introduction	

9.2 Login	
9.3 Live View	
9.4 Playback	
9.5 Configuration	
9.6 Log	
Chapter 10 Appendix	
10.1 Glossary	

Chapter 1 Startup

1.1 Activate Your Device

For the first-time access, you need to activate the video recorder by setting an admin password. No operation is allowed before activation. You can also activate the video recorder via web browser, SADP or client software.

Before You Start

• Power on your device.

For the first-time access, if you do not move the mouse on the interface for one minute, the resolution will be set as 1280*720/60Hz (720P) automatically.

Steps

- 1. Select a language.
- 2. Click Apply.
- 3. Input the same password in **Password** and **Confirm Password**.

	Activation
User Name	admin
*Password	
"Confirm Password	
Password Hint	When you forget your password, the hint will help you remember. It is recommended to set the hint.
Unlock Pattern	
Shutdown	e respect other people's privacy and rights when using product. Activate Auto

Figure 1-1 Activation

Warning

Strong Password recommended-We highly recommend you create a strong password of your own choosing according to the following rules in order to increase the security of your product:
8 to 16 characters.Do not contain the following characters in the password: the user name, 123, admin, no less than 4-digit continuously increasing or decreasing numbers, or no less than 4

continuously same characters.At least 2 of the following types are required: digits, upper-case letters, lower-case letters, and special characters.Risky password is not allowed. We recommend you reset your password regularly, especially in the high security system, resetting the password monthly or weekly can better protect your product.

4. Optional: Set **Password Hint**.

iNote

When you forget your password, the hint will help you remember it. It is recommended to set the password hint.

5. Optional: Set Unlock Pattern.

- 1) Enable Unlock Pattern.
- 2) Use the mouse to draw a pattern among the 9 dots on the screen. Release the mouse when the pattern is done.

iNote

The pattern shall have 4 dots at least. Each dot can be connected for once only.

- 3) Draw the same pattern again to confirm it. When the two patterns match, the pattern is configured successfully.
- 6. Click Activate.
- 7. Optional: Click Auto to automatically configure all the parameters in the wizard.

What to do next

Follow the wizard to set basic parameters.

- For basic system parameters. Refer to *General* for details.
- For general network parameters. Refer to *General* for details.
- For storage device configuration. Refer to **<u>Storage Device</u>** for details.
- For adding network cameras. Refer to *Network Camera* for details.
- For platform configuration. Refer <u>*Hik-Connect*</u> to for details.
- When you forget your password, there are three methods to reset it, including password resetting email, Hik-Connect, and security questions. You can configure the password resetting method. Refer to <u>Set Password Resetting Email</u> and <u>Hik-Connect</u> for details. If you do not set any methods, the auto login window will pop up. If you click Yes, you can log in without password.

1.2 Login

1.2.1 Log in via Unlock Pattern

Steps

1. Right click the mouse to select **Menu** or left click the mouse on live view.



Figure 1-2 Draw the Unlock Pattern

- 2. Draw the pre-defined pattern to enter the menu operation.
 - iNote
 - If you have forgotten your pattern, you click **Forgot My Pattern** or **Switch User** to log in via password.
 - If you have drawn the wrong pattern for more than 5 times, the system will switch to the normal login mode automatically.

1.2.2 Log in via Password

If your video recorder has logged out, you must log in before operating the menu and other functions.

Steps

1. Select User Name.

		×	<
	Welcome		-
	admin	~	
	Password	Ø	
	Auto Login Forgot Pass		ji S
	Login		
Please resp	pect other people's privacy and rights wh	nen using product	

Figure 1-3 Login Interface

- 2. Input password.
- 3. Click Login.

iNote

- When you forget the password of the admin, you can click **Forgot Password** to reset the password.
- If you enter the wrong password 7 times, the current user account will be locked for 60 seconds.

If you check Auto Login, you can log in without password.

Chapter 2 Live View

2.1 GUI Introduction

• Click **Target Detection** at the upper-left corner, and select so results or to display the specified live target detection results. For result details, click **View More**.

INote

- Target Detection is only available for certain models.
- Target Detection is valid when HDD is installed.
- Solution etection, line crossing detection, intrusion detection, and face capture.
- Click 🙋 to start/stop auto-switch. The screen will automatically switch to the next one.
- - window division. Click 🔣 to enter full screen mode.
- Double click a camera to view it in single-screen mode. Double click again to exit single-screen mode.

to select the live view

- Change a camera live view screen by dragging it from its screen to the desired screen.
- Scroll up/down to turn to previous/next screen.
- Position the cursor on a camera to show shortcut menu.



Figure 2-1 Shortcut Menu

Table 2-1 Shortcut Menu Description

Button	Description		
<u>®</u>	Start playing videos recorded in the latest five minutes.		
Ð	Digital zoom. You can adjust zoom-in times and view the desired area.		
必	Click it to enter PTZ control mode.		
2	Turn on/off live view audio.		
11	Switch video stream.		

• In the live view interface, there are icons at the upper-right corner of the screen for each camera, showing the camera recording and alarm status.

Table 2-2 Live View Icon Description

lcon	Description		
>	Alarming (normal event and smart event).		
8	Recording.		

• Right click your mouse to display the shortcut menu.




Figure 2-2 Right Click Shortcut Menu

2.1.1 Customize Window Division

You can also set custom the window division as desired.

Steps

- 1. Open the Live Viewpage.
- 2. Go to Live View \rightarrow Window Division \rightarrow shezhi to open the window division panel.
- 3. Click Edit Nameto edit the layout name.
- 4. Optional: Drag your mouse to select the adjacent windows, and click **Joint** to joint them as a whole window.
- 5. Optional: Select the joint window and click **Restore** to cancel the joint.
- 6. Click Save.
- 7. Optional: Click or drag a division mode to the displaying window to apply the mode for displaying.

2.2 PTZ Control

2.2.1 Configure PTZ Parameter

You shall configure PTZ parameters before controlling a PTZ camera.

Steps

1. Preview a camera in live view and click 🚨 on shortcut menu.



Figure 2-3 PTZ Settings

2. Click 🐵.

3. Set the PTZ camera parameters.

iNote

All parameters should be the same as the PTZ camera.

4. Click OK.

2.2.2 PTZ Control Panel Introduction

lcon	Description	
- C	Direction buttons, and the auto-cycle button.	
Slow — Fast	The speed of the PTZ movement.	
द / द	Zoom -/+.	
	Focus -/+.	
%	Iris -/+.	

Table 2-3 PTZ Panel Description

2.2.3 Customize Preset

Set a preset location where the PTZ camera would point to when an event occurs.

Steps

- 1. Preview a camera in live view and click 🚨 on shortcut menu.
- 2. Select a desired preset in preset list.
- 3. Use direction buttons to wheel the camera to required locations. Adjust zoom and focus as your desire.
- 4. Click 💌.

What to do next

Double click a preset in the preset list to call it.

2.2.4 Customize Patrol

Patrol refers to a path consists of a series of presets with designated sequence. It provides dynamic live image for monitoring several presets.

Steps

- 1. Preview a camera in live view and click on 🚨 shortcut menu.
- 2. Click Patrol.
- 3. Click 🖉 of a desired patrol.

4. Click 🛨.

5. Configure key point parameters, such as the key point No., duration of staying for one key point and speed of patrol. The key point is corresponding to the preset. The preset number determines the order at which the PTZ will follow while cycling through the patrol. **Duration** refers to the time span to stay at the corresponding key point. **Speed** defines the speed at which the PTZ will move from one key point to the next.

KeyPoint			×
	Preset	Preset1	~
	Speed	1	~
	Duration	15	~
		OK Canc	el

Figure 2-4 Patrol Settings

6. Click **OK**.

7. Click Save.

What to do next

Select a patrol and click **()** to call it. The PTZ camera will move according the predefined patrol path.

2.2.5 Customize Pattern

A pattern records the movement path and dwell time in a certain position. When you call a pattern, the PTZ camera will move according to the recorded path.

Steps

- 1. Preview a camera in live view and click 🚨 on shortcut menu.
- 2. Click Pattern.
- 3. Select a pattern.
- 4. Click 💽.
- 5. Use direction buttons to wheel the camera to required locations. Adjust zoom and focus as your desire.
- 6. Click (©). The previous PTZ camera moving path is recorded as a pattern.

What to do next

Select a pattern and click 💿 to call it. The PTZ camera will move according the predefined pattern.

Chapter 3 Playback

3.1 GUI Introduction

Go to Playback.

Normal I I [[01] IPCar [[02] IPCar [[03] IPCar [[04] IPCar [[05] IPCar [[06] IPCar [[06] IPCar [[08] IPCar [[08] IPCar	mera 02 mera 03 mera 04 mera 05 mera 06 mera 07		Slice		
« «	2024 Ju	1			
S M T					
30 1 2					
7 8 9 14 15 16		11 18		13 20	
21 22 23					
28 29 30				3	2000 00 02 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 <> 24 h 🗸
4 5 6					& ଲ ହ ଇ

Figure 3-1 Playback

Table 3-1 Playback Interface Description

Button	Operation	Button	Operation
9	30 s reverse.	6	30 s forward.
5.2 5 3	Full screen.		Start playback.
40	Speed down.	☆	Speed up.
X 1	Speed.	∇	Reverse playback.




Figure 3-2 Timeline

- Position the cursor on the timeline, drag the timeline to position to a certain time.
- Period marked with blue bar contains video. Red bar indicates the video in the period is event video.
- Scroll up/down to zoom out/in timeline.

3.2 Normal Playback

Play back normal videos.

Steps

- 1. Go to **Playback**.
- 2. Select a camera from the camera list.
- 3. Select a date on the calendar for playback.

iNote

The blue triangle at the calendar date corner indicates there are available videos. For example, means video is available. means no video.




Figure 3-3 Playback

4. Optional: Position the cursor on playback window to show control bar.

Figure 3-4 Control Bar

Table 3-2 Button Description

Button	Description	Butto n	Description
1 4 8 9 16	Window division, group the channels and play.	Ð	Zoom in/out playback image.

Button	Description	Butto n	Description
49	Turn on/off audio.		Add tag.
A	Lock/unlock video.	Ж	Clip video.
٨	Show videos that contain human.	ß	Show videos that contain vehicle.
Skip Normal Videos	If you have clicked A/G, the device will hide other videos, and only show and play videos that contain human or vehicle during playback.	R	Display rule frame and target frame.
	Adjust image display effect according to the screen size.	Smart Searc h (🔊)	If you have clicked (a), you can click (a) and configure the detection area to quickly search the human/vehicle information in this area.
	After clicking the button, targets will be displayed on the screen.Click a target to search for pictures that contain the target.Click a picture to play a video before and after that moment.		Multi-window division playback.

Button	Description	Butto n	Description
	i Note Before using this function, you need to enable AcuSearch algorithm for the current channel.		

3.3 Event Playback

When you select the event playback mode, the system will analyze and mark videos that contain the motion detection, line crossing detection, or intrusion detection information, .

Before You Start

- Ensure the camera has enabled **Dual-VCA**. You can enable it via the camera web browser interface in **Configuration** → **Video/Audio** → **Display Info. on Stream**.
- Ensure your video recorder has enabled Save VCA Data. You can enable it in Configuration → Record → Advanced.

- 1. Go to Playback.
- 2. Click Event.
- 3. Select a camera.
- 4. Position the cursor on playback window to show control bar.

Button	Description	Button	Description
Д	Add tag.	Ð	Zoom in/out playback image.
*	Clip video.	A	Lock/unlock video.
ନ୍ଦ	Configure detection area.	22	Turn on/off audio.

- 5. Click 2 to set detection areas of line crossing detection, intrusion detection, or motion detection.
- 6. Click 💽 to search videos. Videos meet the detection rule requirement will be marked in red.
- 7. Click 🔯 to configure the play strategy.

Skip Normal Videos

If it is enabled, videos without smart information will not be played.

Normal Video

Set normal video playback speed. The option is only valid when **Do not Play Normal Videos** is unchecked.

Play Speed of Smart/Custom Video

Set playback speed of videos with smart information. The option is only valid when **Do not Play Normal Videos** is enabled.

3.4 Slice Playback

Divide the video into slices and play them back.

Steps

1. Go to Playback \rightarrow Slice Playback.



Figure 3-5 Slice Playback

- 2. Select a camera from the camera list.
- 3. Select a month, a date, and an hour on the calendar for playback.

iNote

The blue triangle at the calendar date corner indicates there are available videos. For example, means video is available. means no video.

The retrieved video will be divided into one-hour slices for playback.

- 4. Optional: Select an one-hour slice and click 💽 to divide it into one-minute slices for playback.
- 5. Click a slice to play back the video on the right.

lcon	Name	Description
R	AcuSearch	After clicking the button, targets will be displayed on the screen.Click a target to search for pictures that contain the target.Click a picture to play a video before and after that moment.
t	Export Video	Click to export the video.
8	Display VCA Info	Display rule frame and target frame. i Note Prerequisite: The channel has been added and can be previewed. VCA configuration has been completed on the camera or device.
Ð	Enable Self- Adaptive Resolution	Adjust the image display effect according to the screen size.
Ŷ	Audio Control	Turn on/off audio and adjust the volume.

Table 3-4 Slice Playback Icon Description

3.5 Back up Clip

You can clip videos during playback. Video clips can be exported to the backup device (USB flash drive, etc.).

Before You Start

Connect a backup device to your video recorder.

- 1. Start playback. Refer to *Normal Playback* for details.
- 2. Click 🐰.

3. Set the start and end time. You can also adjust cursors on the time bar to set the time period.

- 4. Click Save.
- 5. Select the backup device and folder.
- 6. Click **Save** to export the clip to backup device.

Chapter 4 Search File

Steps

- 1. Go to Search.
- 2. Select a search type (video, picture, event, etc.).
- 3. Set search conditions.
- 4. Optional: Click Quick Backup to quickly export videos to the device.

Note

Quick backup is available for video and event search.

- 5. Click Search.
 - Click 💿 to play the video.
 - Click 🖆 to lock the file. Locked file will not be overwritten.
 - Select file(s), and click **Export** to export file(s) to backup device.

4.1 Search Human by Face Picture

You can search human records by the provided face picture.

Before You Start

Ensure you have enabled face picture comparison.

Steps

1. Go to **Search** \rightarrow **Human**.

Search Method	O By Tir	ne 🧿	By Pictu	ıre					
"Select Picture	5	2	Tr Uploa	d from L	ocal i	Lupload	from Fi	ace Picture	Librai
"Start/End Time	27-08-2								
Channel	A1	A2	A3	A4	A5	A6	A7	A8	
	D1	D2	D3	D4	D5	D6	D7	D8	
	D9	D10	D11	D12					
Similarity	>=		•	- 80					
	Sea	rchi	Re	set					

Figure 4-1 Search Human by Face Picture

- 2. Set Search Method by By Picture.
- 3. Upload a face picture.
 - Click Upload from Local to upload a face picture from a local storage device, such as USB flash drive.
 - Click **Upload from Face Picture Library** to upload a face picture from a face picture library.

iNote

- Only JPG and JPEG formats are supported.
- Each picture size should be less than 1 MB.
- The picture resolution shall be between 80 × 80 and 1920 × 1080.
- 4. Set the start time and end time.

5. Set Similarity.

Similarity

Similarity value ranges from 0 to 100. Device will analyze the similarity between the detected face picture and face pictures in the library. When the similarity reaches the threshold value, the face picture comparison succeeded, and the face picture is recognized.

6. Click Search.

4.2 Quick Backup

Before You Start

Connect a backup device to your video recorder.

- 1. Go to Search.
- 2. Set search conditions.
- 3. Click Quick Export.
- 4. Select backup device and path.
- 5. Click **OK** to start exporting.

Chapter 5 Configuration (Easy Mode)

Easy mode contains basic configurations. Go to Configuration, and click Easy Mode.

5.1 System Configuration

5.1.1 General

You can configure the output resolution, system time, etc.

Steps

- 1. Go to **Configuration** \rightarrow **System** \rightarrow **General**.
- 2. Configure the parameters as your desire.

Wizard

The wizard will pop up after the device starts up.

Password-Free Login

You can log in without password.

NTP Time Sync

Network time protocol (NTP) is a networking protocol for time synchronization. The device can connect to NTP (network time protocol) server to sync time.

Interval (min)

Time interval between two time synchronization with NTP server.

NTP Server

IP address of the NTP server.

3. Click Apply.

5.1.2 User

Add User

There is a default account: Administrator. The administrator user name is **admin**. Administrator has the permission to add, delete, and edit user. Guest user only has live view, playback, and log search permission.

- 1. Go to **Configuration** \rightarrow **System** \rightarrow **User**.
- 2. Click Add and confirm your admin password.

- 3. Enter user name.
- 4. Select user level.

5. Enter the same password in **Create Password** and **Confirm**.

Warning

We highly recommend you create a strong password of your own choosing in order to increase the security of your product.

8 to 16 characters.Do not contain following characters in the password: the user name, 123, admin, no less than 4-digit continuously increasing or decreasing numbers, or no less than 4 continuously same characters.At least 2 of the following types are required: digits, upper-case letters, lower-case letters, and special characters.Risky password is not allowed. We recommend you reset your password regularly, especially in the high security system,

resetting the password monthly or weekly can better protect your product.

6. Configure user permissions.

- 7. Click **OK**.
 - Click 🖉/🔟 to edit/delete user.

Set Password Resetting Email

When you forget your login pattern and password, the device will send an email contains verification code to your email for password resetting.

Steps

- 1. Go to **Configuration** \rightarrow **System** \rightarrow **User**.
- 2. Click Password Resetting Email.
- 3. Enter admin password for authorization.
- 4. Enter an email address.
- 5. Click **OK**.

Reset Password

You can reset your password when you forgot your login pattern and password.

- 1. Click Forgot Password at the password login interface.
- 2. Click **Next** if you agree the Privacy Policy, you can scan the QR code to read it.
- 3. Follow the wizard to reset password.

5.1.3 Exception

You can receive exception events hint in alarm center, and set exception linkage actions.

Steps

- 1. Go to **Configuration** \rightarrow **System** \rightarrow **Exception**.
- 2. Optional: Configure event hint. When the set events occur, you will receive hints in alarm center.
 - 1) Enable Event Hint.
 - 2) Click 🕘 at the upper-right corner of local menu to enter alarm center.
 - 3) Select an event type.
 - 4) Click Set to select events to hint.
- 3. Set Exception Type
- 4. Select **Normal Linkage** type for exception linkage actions.

Event Hint	
Exception Type HDD Full	~
Normal Linkage	Trigger Alarm Output
Buzzer Alarm	
□ Notify Surveillance Center	
□ Send Email	
Apply	

Figure 5-1 Exception

5. Click Apply.

5.2 Network Configuration

5.2.1 General

You shall properly configure the network settings before operating the device over network.

Steps

1. Go to **Configuration** \rightarrow **Network** \rightarrow **General**.

DHCP (IPv4)	
IP Address	THE PARTY OF
Subnet Mask	Second Street
Default Gateway	diment remains
Auto Obtain DNS	
Preferred DNS Server	pine circle
Alternate DNS Server	Harring .
	Apply

Figure 5-2 Network

2. Set network parameters.

DHCP

If the DHCP server is available, you can enable **DHCP** to automatically obtain an IP address and other network settings from that server.

Auto Obtain DNS

If **DHCP** is enabled. You can enable **Auto Obtain DNS** to automatically obtain **Preferred DNS Server** and **Alternate DNS Server**.

3. Click Apply.

5.2.2 Hik-Connect

Hik-Connect provides mobile phone application and platform service to access and manage your connected devices, which enables you to get a convenient remote access to the video security system.

```
1. Go to Configuration \rightarrow Network \rightarrow Hik-Connect.
```

- 2. Turn on **Enable**. The service terms will pop up.
 - 1) Read the service terms and privacy statement.
 - 2) Check I have read and agree to Service Terms and Privacy Statement. if you agree with the service terms and privacy statement.

3) Click **OK**.

- 3. Click 🖉 to set verification code.
- 4. Optional: Enable **Platform Time Sync**, the device will sync time with the platform server instead of NTP server.
- 5. Optional: Enable **Stream Encryption**. It requires to enter verification code in remote access and live view after this function is enabled.
- 6. Optional: Edit Server IP.
- 7. Optional: Enable **Sub-Stream Self-Adaptive Bitrate**. When the network environment is poor, the device would automatically adjust video bitrate to ensure playing fluency.
- 8. Bind your device with a Hik-Connect account.
 - 1) Use a smart phone to scan the QR code, and download Hik-Connect app. You can also download it from <u>https://appstore.hikvision.com</u>, or the QR code below. Refer to *Hik-Connect Mobile Client User Manual* for details.



Figure 5-3 Download Hik-Connect

2) Use Hik-Connect to scan the device QR, and bind the device.

iNote

- If the device is already bound with an account, you can click **Unbind** to unbind with the current account.
- You can also use the QR code in 📰 at the upper-left corner to download Hik-Connect and bind your device.

9. Click **Apply**.

Result

- If your device is connected with Hik-Connect platform, **Connection Status** will be **Online**.
- If your device is bound with a Hik-Connect account, **Bind Status** will be **Yes**.

What to do next

You can access your video recorder via Hik-Connect.

5.2.3 Email

Set an email account to receive event notification.

Before You Start

- Ensure SMTP service is available for your email.
- Configure your network parameters. Refer to <u>General</u> for details.

Steps

1. Go to **Configuration** \rightarrow **Network** \rightarrow **Email**.

Server Authentication			
User Name			
Password			
SMTP Server	Custom	~	
SMTP Server			
SMTP Port	25		
SSL/TLS			
Attached Picture			
Sender			
Sender's Address			
Select Receivers	Receiver 1	~	
Receiver			
Receiver's Address			
	Apply	Test	

Figure 5-4 Email

2. Set email parameters

Server Authentication

Check it to enable the server authentication feature.

User Name

The user account of email sender for SMTP server authentication.

Password

The password of email sender for SMTP server authentication.

SMTP Server/SMTP Port

After selecting the **SMTP Sever**, its address and port will be showed automatically. You can also edit them according to actual needs.

SSL/TLS

(Optional) Enable SSL/TLS if it is required by the SMTP server.

Attached Picture

(Optional) If events are triggered, it will send images as email attachment.

Sender

The sender name.

Sender's Address

The sender's email address.

Select Receiver

Select a receiver. Up to 3 receivers are available.

Receiver

The receiver name.

Receiver's Address

The receiver's email address.

iNote

For network cameras, the event images are directly sent as the email attachment. One network camera only sends one picture.

3. Optional: Click Test to send a test email.

4. Click **Apply**.

5.3 Camera

5.3.1 Network Camera

Configure Signal Input

For certain digital video recorder models, you can configure the analog and IP signal input types.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Analog** \rightarrow **Analog**.
- 2. Select signal input type as **HD/CVBS** or **IP** for each channel.

HD/CVBS

Four types of analog signal inputs including Turbo HD, AHD, HDCVI, and CVBS can be connected randomly for the channel.

IP

Network camera can be connected for the channel.

No.	I I HD/CVBS	I OIP I
A1		0
A2		0
A3		0
A4		0
A5		0
A6		0
① Max. IP camera number 4		

Figure 5-5 Signal Input Type

3. Click **Apply**. You can view the maximum network camera accessible number in **Max. IP Camera Number**.

Add Network Camera by Device Password

Add network cameras which the password is the same as your video recorder.

Before You Start

- Ensure your network camera is on the same network segment with your video recorder.
- Ensure the network connection is valid and correct. Refer to <u>General</u> for details.
- Ensure the network camera password is the same as your video recorder.

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **IP Camera**. The online cameras on the same network segment with your video recorder are displayed in **Online Device List**.
- 2. Select a desired network camera.
- 3. Click Ħ to add the camera.

iNote

If the camera is inactive, the device will activate it automatically with the password you have set during device activation.

4. Optional: If your network camera is not on the same network segment with the DVR and supports ONVIF protocol, click **Advanced Search** and fill in the first three octets of the camera IP address to add the camera(s).

Add Network Camera Manually

Before You Start

- Ensure your network camera is on the same network segment with that of your video recorder.
- Ensure the network connection is valid and correct.
- Ensure the network camera is activated.

Steps

- 1. Go to Configuration \rightarrow Camera \rightarrow IP Camera.
- 2. Click 🛨 in Added Device List.
- 3. Set network camera parameters, including IP address, protocol, management port, etc.
- 4. Optional: Double click Camera Name to edit name.

iNote

Camera name can be edited only when the camera status is online.

- 5. Optional: Enable **Use Camera Activation Password** to use the device password to add network camera(s).
- 6. Optional: Click Add More to add another network camera.
- 7. Click Add.

Add IP Camera (Custom)				×
O Refresh				
No. ≑	∣ Status	Protocol	∣ Manageme	ent Port ∣Devic
IP Camera Address				
Channel No.	2			~
Protocol	HIKVISION			~
Management Port	8000			
Transfer Protocol	Auto			~
User Name	admin			
Camera Password				
Use Camera Activation				
		Add More	Add	Cancel

Figure 5-6 Add Network Camera

Edit Connected Network Camera

You can edit the IP address, protocol and other parameters of the added network cameras.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **IP Camera**.
- 2. Click 🖉 to edit the selected camera.

Channel Port

If the connected device is an encoding device with multiple channels, you can select the channel port No. to choose a connecting channel.


3. Click OK.

5.3.2 OSD Settings

Configure OSD (On-Screen Display) settings for the camera, including date format, camera name, etc.

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **OSD**.
- 2. Select a camera.

Camera	[D8] Camera 01	×		
04-24-2020 Fri 11:24:27		8	Camera Name	Camera 01
			Display Name	
			Display Date	
			Display Week	••
1000			Date Format	MM-DD-YYYY ~
100000000			Time Format	24-hour ~
		anera Ul	Display Mode	Non-Transparent & Not Fla ~
Apply				



- 3. Set parameters as your desire.
- 4. Drag the text frames on the preview window to adjust the OSD position.
- 5. Click Apply.

5.3.3 Motion Detection

Motion Detection enables the video recorder to detect the moving objects in the monitored area and trigger alarms.

Steps

- 1. Go to Configuration \rightarrow Camera \rightarrow Motion Detection.
- 2. Select a camera.
- 3. Check Enable.
- 4. Set the motion area: Click Draw Area or Clear to draw or clear areas.

The operation may differ according to different models.

- 5. Adjust **Sensitivity**. Sensitivity allows you to calibrate how readily movement triggers the alarm. A higher value results in the more readily to triggers motion.
- 6. Set analysis mode as **AI** or **PIR**.

AI

The motion event will be analyzed by your device.

PIR

The motion event will be analyzed by certain analog PIR cameras.

- 7. Optional: Set **Detection Target** as **Human** or **Vehicle** to discard alarms which are not triggered by human or vehicle.
- 8. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 9. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.

iNote

10. Click Apply.

5.4 Configure Alarm Linkage Action

Alarm linkage actions will be activated when an alarm or exception occurs.

Steps

1. Click Linkage Action.

2. Set normal linkage actions, alarm output linkage actions, trigger channel, etc.

Alarm Pop-up Window

The local monitor will pop up the alarming channel image when an alarm is triggered. It requires to select the alarming channel(s) in **Trigger Channel**.

Buzzer Alarm

It will trigger a buzzer beep when an alarm is triggered.

Notify Surveillance Center

The device will send an exception or alarm signal to the remote client software when an alarm is triggered.

Send Email

It will send an email with alarm information when an alarm is triggered.

Trigger Channel

The selected channel(s) will start recording. It requires to configure the recording schedule for the channel in **Configuration** \rightarrow **Record** \rightarrow **Schedule**.

3. Click Apply.

5.5 Configure Arming Schedule

Steps

- 1. Select Arming Schedule.
- 2. Choose one day of a week and set the time segment. Up to eight time periods can be set within each day.

iNote

Time periods shall not be repeated or overlapped.




Figure 5-8 Set Arming Schedule

3. Click Apply.

5.6 Recording Management

5.6.1 Storage Device

Initialize HDD

A newly installed hard disk drive (HDD) must be initialized before it can be used to save videos and information.

Before You Start

Install at least an HDD to your video recorder. For detailed steps, refer to Quick Start Guide.

Steps

- 1. Go to **Configuration** \rightarrow **Record** \rightarrow **Storage**.
- 2. Select an HDD.
- 3. Click Init.

Repair Database

Repair an HDD that with error in database. Please operate it with the help of professional technical support.

Add Network Disk

You can add the allocated NAS or IP SAN disk to the video recorder, and use it as a network HDD.

- 1. Go to **Configuration** \rightarrow **Record** \rightarrow **Storage**.
- 2. Click Add.
- 3. Select NetHDD.

- 4. Set Type as NAS or IP SAN.
- 5. Enter **NetHDD IP** address.
- 6. Click **Q** to search the available disks.

Custom Add	×
NetHDD Net	HDD 1 ~
Type NAS	s ~
NetHDD IP	
NetHDD Directory	٩
No. Directory	
	OK Cancel

Figure 5-9 Add NetHDD

- 7. Select NAS disk from the list, or manually enter the directory in **NetHDD Directory**.
- 8. Click **OK**. The added NetHDD will be displayed in the storage device list.

5.6.2 Configure Recording Schedule

Video recorder will automatically start/stop recording according to the configured schedule.

Configure Continuous Recording

- 1. Go to **Configuration** \rightarrow **Record** \rightarrow **Parameter**.
- 2. Set the continuous main stream/sub-stream recording parameters for the camera. Refer to *Configure Recording Parameter* for details.
- 3. Go to **Configuration** \rightarrow **Record** \rightarrow **Schedule**.
- 4. Select recording type as **Continuous**. Refer to <u>Edit Schedule</u> for details.

Configure Event Recording

You can configure the recording triggered by the motion detection.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Motion**.
- 2. Configure the event detection and select the channels to trigger the recording when an event occurs.
- 3. Go to **Configuration** \rightarrow **Record** \rightarrow **Parameter**.
- 4. Set the continuous main stream / sub-stream recording parameters for the camera. Refer to <u>Configure Recording Parameter</u> for details.
- 5. Go to **Configuration** \rightarrow **Record** \rightarrow **Schedule**.
- 6. Select recording type as **Event**. Refer to <u>*Edit Schedule*</u> for details.

Edit Schedule

Steps

1. Go to Configuration \rightarrow Record \rightarrow Schedule.




Figure 5-10 Recording Schedule

Continuous

Continuous recording.

Event

Recording is triggered by events.

- 2. Select a camera in Camera No.
- 3. Turn on **Enable**.
- 4. Configure the recording schedule.

Edit Schedule 1. Click Edit.

2. Select a day to configure in Weekday.

- 3. To set an all-day recording schedule, check **All Day** and select schedule type.
- 4. To set other schedules, uncheck **All Day**, and set **Start/End Time** and schedule type.

iNote

Up to 8 periods can be configured for each day. And the time periods cannot be overlapped with each other.

5. Click **OK** to save the settings and go back to upper level menu.

Draw Schedule

- 1. Click to select schedule type as **Continuous** or **Event**.
- 2. On the table, drag the mouse on the desired period to draw a colored bar.
- 5. Click Apply.

5.6.3 Configure Recording Parameter

Steps

- 1. Go to **Configuration** \rightarrow **Record** \rightarrow **Parameter**.
- 2. Configure recording parameters.

Main Stream

Main stream refers to the primary stream that affects data recorded to the hard disk drive and will directly determine your video quality and image size. Comparing with the substream, the main stream provides a higher quality video with higher resolution and frame rate.

Sub-Stream

Sub-stream is a second codec that runs alongside the mainstream. It allows you to reduce the outgoing internet bandwidth without sacrificing your direct recording quality. Sub-stream is often exclusively used by smartphone applications to view live video. Users with limited internet speeds may benefit most from this setting.

Resolution

Image resolution is a measure of how much detail a digital image can hold: the greater the resolution, the greater the level of detail. Resolution can be specified as the number of pixel-columns (width) by the number of pixel-rows (height), e.g.,1024×768.

Frame Rate

Frame rate refers to how many frames are captured each second. A higher frame rate is advantageous when there is movement in the video stream, as it maintains image quality

throughout.

Max. Bitrate

Set the maximum bit rate. The bit rate (in Kbit/s or Mbit/s) is often referred to as speed, but actually defines the number of bits/time unit and not distance/time unit.

Encoding Type

Set the video encoding type.

Enable H.265+

Enable or Disable H.265+.

iNote

Higher resolution, frame rate, and bitrate provide you better video quality, but it also requires more internet bandwidth and uses more storage space on the hard disk drive.

3. Click Apply.

Chapter 6 Configuration (Expert Mode)

Go to **Configuration**, and click **Expert Mode** at the lower-left corner.

6.1 System Configuration

6.1.1 General

Configure Basic Settings

You can configure the video quality mode, output resolution, mouse pointer speed, wizard, etc. Go to **Configuration** \rightarrow **System** \rightarrow **General** \rightarrow **Basic Settings**, configure the parameters as your desire, and click **Apply**.

VGA/HDMI Resolution

Select the output resolution, which must be the same with the resolution of the VGA/HDMI display.

Video Quality Mode

The default mode is standard.

Mouse Pointer Speed

Set the speed of mouse pointer. 4 levels are configurable.

Password-Free Login

You can log in without password.

Wizard

The wizard will pop up after the device starts up.

Region & Time Settings

You can configure the language, system time, region, etc.

Configure More Settings

You can configure your device name, lock screen time, output mode, etc. Go to **Configuration** \rightarrow **System** \rightarrow **General** \rightarrow **More Settings**, configure the parameters as your desire, and click **Apply**.

Device Name

Edit the video recorder name.

Device No.

The number is required in the connection with remote control, network keyboard, etc. Edit the serial number of video recorder. The device number ranges from 1 to 255, and the default value is 255.

Lock Screen

Set timeout time for lock screen.

Menu Output Mode

Choose output to display local menu.

CVBS Output Brightness

Set brightness for the CVBS output.

Output Standard

Set it to NTSC or PAL, it must be the same with the video input standard.

1080P Lite Mode

When **1080P Lite Mode** is enabled, the encoding resolution at 1080P Lite (real-time) is supported. If not, up to 1080P (non-real-time) is supported.

6.1.2 Live View

Configure General Parameters

You can configure the output interface, mute or turning on the audio, event output interface, etc.

Steps

1. Go to **Configuration** \rightarrow **System** \rightarrow **Live View** \rightarrow **General**.

Output Interface	VGA/Channel-Zero	~
Window Division	4 * 4	~
Auto-Switch Interval	Close	~
Alarm Pop-up Output	HDMI	~
Alarm Pop-up Delay	10s	~
Audio		
Volume	1	5 2
	Apply	

Figure 6-1 Live View-General

2. Configure the Live View parameters.

Window Division

Select the live view window division.

Auto Switch Interval

The time to dwell in a camera before switching to next camera when auto-switch in live view is enabled.

Alarm Pop-up Output

Select the output to show alarm video.

Alarm Pop-up Delay

Set the time to show alarm event image.

Audio

Turn on/off audio output for the selected video output.

Volume

Adjust the live view, playback, and two-way audio volume for the selected video output interface.

3. Click Apply.

Configure Live View Layout

Steps

- 1. Go to **Configuration** \rightarrow **System** \rightarrow **Live View** \rightarrow **View**.
- 2. Set Output Interface.
- 3. Select a window, and double click a camera the list you would like to display. + means no camera is displayed on the window.
- 4. Optional: Click 🚯 or 🔯 to start or stop live view of all cameras.
- 5. Click Apply.

Configure Channel-Zero Encoding

Enable the channel-zero encoding when you need to get a remote view of many channels in real time from a web browser or CMS (Client Management System) software, in order to decrease the bandwidth requirement without affecting the image quality.

- 1. Go to Configuration \rightarrow System \rightarrow Live View \rightarrow General.
- 2. Set Video Output Interface as Channel-Zero.
- 3. Go to Configuration \rightarrow System \rightarrow Live View \rightarrow Channel-Zero.

Digital Video Recorder User Manual

Enable		
Frame Rate	Full Frame	~
Max. Bitrate Mode	General	~
Max. Bitrate(Kbps)	1792	~
	Apply	

Figure 6-2 Channel-Zero

4. Turn on **Enable**.

- 5. Configure **Frame Rate**, **Max. Bitrate Mode**, and **Max. Bitrate**. The higher frame rate and bitrate require higher bandwidth requirement.
- 6. Click Apply.

6.1.3 User

Refer to User for details.

6.2 Network Configuration

6.2.1 General

TCP/IP

TCP/IP must be properly configured before you operate video recorder over network.

Steps

- 1. Go to **Configuration** \rightarrow **Network** \rightarrow **General** \rightarrow **TCP/IP**.
- 2. Configure network parameters.

Working Mode

Multi-address Mode

The parameters of the two NIC cards can be configured independently. You can select LAN1 or LAN2 in the NIC type field for parameter settings. You can select one NIC card as default route. And then the system is connecting with the extranet and the data will be forwarded through the default route.

Net-fault Tolerance Mode

The two NIC cards use the same IP address, and you can select the Main NIC to LAN1 or LAN2. By this way, in case of one NIC card failure, the video recorder will automatically enable the other standby NIC card so as to ensure the normal running of the whole system.

Load Balance Mode

By using the same IP address and two NIC cards share the load of the total bandwidth, which enables the system to provide two Gigabit network capacity.

iNote

Working mode is only available for certain models.

NIC Type

Select NIC type as your desire. If your device supports Wi-Fi dongle function, the NIC of Wi-Fi dongle would be selectable after a suitable Wi-Fi dongle is installed.

DHCP

If the DHCP server is available, you can check **Enable DHCP** to automatically obtain an IP address and other network settings from that server.

MTU

The maximum transmission unit (MTU) is the size of the largest network layer protocol data unit that can be communicated in a single network transaction.

Default Route

Select a route as your desire. If your device supports Wi-Fi dongle function, the route of Wi-Fi dongle would be selectable after a suitable Wi-Fi dongle is installed.

Auto Obtain DNS

If DHCP is checked. You can check Obtain DNS Automatically to obtain Preferred DNS Server and Alternate DNS Server.

3. Click **Apply**.

DDNS

Dynamic domain name server (DDNS) maps dynamic user IP addresses to a fixed domain name server.

Before You Start

Register DynDNS, PeanutHull and NO-IP services with your ISP.

Steps

1. Go to **Configuration** \rightarrow **Network** \rightarrow **General** \rightarrow **DDNS**.

Digital Video Recorder User Manual

Enable	
DDNS Type	DynDNS ~
Server Address	
Device Domain Name	
User Name	
Password	
Status	DDNS is disabled.
	Apply

Figure 6-3 DDNS

- 2. Turn on **Enable**.
- 3. Select a DDNS type.
- 4. Enter parameters including service address, domain name, etc.
- 5. Click Apply.

What to do next

You can view DDNS status in **Status**.

NAT

Two ways are provided for port mapping to realize the remote access via the cross-segment network, UPnP[™] and manual mapping.

Before You Start

Enable the UPnP[™] function of your router if UPnP[™] is required. When the device network working mode is multi-address, the default device route should be on the same network segment as the LAN IP address of the router.

Steps

1. Go to **Configuration** \rightarrow **Network** \rightarrow **General** \rightarrow **NAT**.

Enable					
Mapping Type	Manual				
O Refresh					
Туре	Operation	External Port	External IP Address	Internal Port	∣ UPnP Status
HTTP Port	L	80	0.0.0.0	80	Inactive
RTSP Port	l	554	0.0.0.0	554	Inactive
Server Port	L	8000	0.0.0.0	8000	Inactive
HTTPS Port	L	443	0.0.0.0	443	Inactive
HIK Cloud P2P Comman	l	9010	0.0.0.0	9010	Inactive
Cloud P2P Data Port	2	9020	0.0.0.0	9020	Inactive
Apply					

Figure 6-4 NAT

2. Turn on **Enable**.

3. Select Mapping Type as Manual or Auto

Auto	The port mapping items are read-only, and the external ports are set
	by the router automatically. You can click Refresh to get the latest
	status of the port mapping.

- Manual
 Select an external port type. Click to edit External Port. You can use the default external port No., or change it according to actual requirements. External Port indicates the port No. for port mapping in the router.
 The value of the RTSP port No. should be 554 or between 1024 and 65535, while the value of the other ports should be between 1 and 65535 and the value must be different from each other. If multiple devices are configured for the UPnP[™] settings under the same router, the value of the port No. for each device should be unique.
- 4. Set the virtual server of your router, including internal source port, external source port, etc. The virtual server parameters shall be corresponding with your device port.

Wi-Fi

For certain models, after installing a Wi-Fi dongle to your device, the device would be able to connect to a wireless network, and the channels in your device can be viewed thorough Wi-Fi. For example, if your device is connected with several network cameras or analog cameras (Wi-Fi network cameras currently cannot be connected), after the device is connected to a wireless network, you would be able to access your device and view the connected channels through Wi-Fi.

Before You Start

- Prepare a suitable Wi-Fi dongle, and insert it in to the USB interface at the rear panel.
- Ensure your device support this function.

Steps

1. Go to Configuration \rightarrow Network \rightarrow General \rightarrow Wi-Fi.

iNote

The Wi-Fi setting interface will automatically pop up when you insert the Wi-Fi dongle for the first time.

2. Connect to a wireless network.

Connect to an Automatically Searched Wireless Network		Double click the wireless network from the list as you desired. Set wireless network parameters. Click OK .
Connect to a Customized Wireless Network		Click Custom Adding . Set wireless network parameters. Click OK .
Connect to a Wireless Network with WPS (Wi-Fi Protected Setup)	2.	Click WPS Settings . Check Enable WPS . Set wireless network parameters. Click Apply .

iNote

If you requires to edit or forget the network, double click the connected network, and edit it as your desire.

After connecting to an available wireless network, you can view the connection result in **Connection Status**.

- 3. Go to Configuration \rightarrow Network \rightarrow General \rightarrow TCP/IP.
- 4. Set Select NIC and Default Route as WLAN0.
- 5. Check Enable Wi-Fi.
- 6. Set other network parameters.
- 7. Click Apply.

NTP

Your device can connect to a network time protocol (NTP) server to ensure that the system time is accurate.

Steps

1. Go to Configuration \rightarrow Network \rightarrow General \rightarrow NTP.

2. Turn on Enable.

3. Enter the parameters.

Interval

Time interval between two time synchronization with NTP server.

NTP Server

IP address of the NTP server.

4. Click Apply.

Log Server Settings

Upload Logs to the Server

You can upload system logs to the server for backup.

Steps

1. Go to Configuration \rightarrow Network \rightarrow General \rightarrow Log Server Settings.

Enable	-	
Upload Time Interval (h)	1	
Server IP Address		
Port	514	
	Apply	Test

Figure 6-5 Log Server Settings

- 2. Turn on Enable
- 3. Set Upload Time Interval, Server IP Address, and Port.
- 4. Optional: Click Test to test if parameters are valid.
- 5. Click **Apply**.

Ports (More Settings)

Set different port types to enable relevant functions as your desire.

Go to Configuration \rightarrow Network \rightarrow General \rightarrow More Settings.

Alarm Host IP/Port

The device will send the alarm event or exception message to the alarm host when an alarm is triggered. The remote alarm host must have the client management system (CMS) software installed.

Alarm Host IP refers to the IP address of the remote PC on which the CMS software (e.g., iVMS-

4200) is installed, and the Alarm Host Port (7200 by default) must be the same as the alarm monitoring port configured in the software.

Server Port

For remote client software access. Ranges from 2000 to 65535. The default value is 8000.

HTTP Port

For remote web browser access. The default value is 80.

Multicast IP

Multicast can be configured to enable live view for cameras that exceed the maximum number allowed through network. A multicast IP address covers Class-D IP ranging from 224.0.0.0 to 239.255.255.255 and it is recommended to use the IP address ranging from 239.252.0.0 to 239.255.255.255.

When adding a device to the CMS software, the multicast address must be the same as that of the device.

RTSP Port

RTSP (Real Time Streaming Protocol) is a network control protocol designed for use in entertainment and communications systems to control streaming media servers. The port is 554 by default.

Output Bandwidth Limit

You can check the checkbox to enable output bandwidth limit.

IP Address Self-Adaption

After enabled, when the device IP address conflict, it will be automatically changed; when the network camera and the LAN are not in the same IP address segment, the IP address of the connected network camera will be automatically edited to the current IP address segment.

Output Bandwidth

After enable the output bandwidth limit, input the output bandwidth.

iNote

- The output bandwidth limit is used for the remote live view and playback.
- The default output bandwidth is the maximum limit.

Alarm Host IP	
Alarm Host Port	0
Server Port	8000
HTTP Port	80
Multicast IP	
RTSP Port	554
	Apply

Figure 6-6 Port Settings

6.2.2 Platform Access

Hik-Connect

Go to **Configuration** \rightarrow **Network** \rightarrow **Platform Access**. Refer to <u>*Hik-Connect*</u> for details.

ISUP

SDK is based on Intelligent Security Uplink Protocol (ISUP). It provides APIs, library files, and commands for the third-party platform to access devices such as NVRs, speed domes, DVRs, network cameras, mobile NVRs, mobile devices, decoding devices, etc. With this protocol, the third-party platform can realize functions like live view, playback, two-way audio, PTZ control, etc.

Steps

- 1. Go to Configuration \rightarrow Network \rightarrow Platform Access.
- 2. Set Type as ISUP.

Digital Video Recorder User Manual

Туре	ISUP ~
Enable	
Server Address	
Server Port	7660
Online Status	Offline
Device ID	787015728
Version	ISUP5.0 V
Encryption Password	******
	Apply

Figure 6-7 ISUP

3. Turn on **Enable**.

iNote

Enabling ISUP will disable other platform access.

4. Set the related parameters.

Server Address

The platform server IP address.

Server Port

The platform server port, ranges from 1024 to 65535. The actual port shall be provided by the platform.

Device ID

The Device ID shall be provided by the platform.

Version

ISUP protocol version, only V5.0 is available.

Encryption Password

Encryption password is required when using ISUP V5.0 version, it provides more secure communication between the device and platform. Enter it for verification after the device is registered to the ISUP platform.

5. Click **Apply** to save the settings and restart the device.

What to do next

You can see the online status (online or offline) after the device is restarted.

OTAP Service

Steps

- 1. Go to Configuration \rightarrow Network \rightarrow Platform Access.
- 2. Set Type as OTAP Service.
- 3. Turn on **Enable**.

Note

Enabling OTAP service will disable other platform access.

4. Set the related parameters.

Server Address

The platform server IP address.

Port

The platform server port ranges from 1 to 65535. The default value is 7800. The actual port shall be provided by the platform.

Device ID

The Device ID shall be provided by the device.

Кеу

The key is used for verification when the server receives the registration information. 6 to 12 characters are allowed for the key. The default key is abc12345.

5. Click **Apply** to save the settings and restart the device.

What to do next

You can see the registration status (online or offline) after the device is restarted.

6.2.3 Email

Go to **Configuration** \rightarrow **Network** \rightarrow **Email**. Refer to <u>*Email*</u> for details.

6.3 Camera Management

6.3.1 Configure Signal Input

For certain digital video recorder models, you can configure the analog and IP signal input types.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Analog**, or click **Edit** at the upper-right corner in **Configuration** \rightarrow **Camera**.
- 2. Select signal input type as **HD/CVBS** or **IP**.

HD/CVBS

Four types of analog signal inputs including Turbo HD, AHD, HDCVI, and CVBS can be connected randomly for the channel.

IP

Network camera can be connected for the channel.

No.	I I HD/CVBS	I OIP
A1		0
A2		0
A3		0
A4		0
A5		0
A6		0
Max. IP camera number 4		

Figure 6-8 Signal Input Type

3. Click **Apply**. You can view the maximum network camera accessible number in **Max. IP Camera Number**.

6.3.2 Network Camera

Add Automatically Searched Online Network Camera

Add the network cameras to your video recorder.

Before You Start

- Ensure your network camera is on the same network segment with your video recorder.
- Ensure the network connection is valid and correct.

• Ensure the network camera password is the same as your video recorder.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click **Online Device List**. The online cameras on the same network segment will be displayed in the list.

I ∨ Online I	Device List							Free bandwidth: 96Mbps
+ Add -			lit IP OR	Refresh ಕ	器 Advanced Sear	ch		
	o. ≑	ress ≑ ∣St	atus ∣Oper	ration Pr	otocol	Management Port	Device Model	∣ Serial No.

Figure 6-9 Online Device

3. Optional: Click **Edit IP** to edit camera IP addresses in batch. The system will allocate IP addresses to the selected cameras in order.

iNote

- Ensure the selected cameras are activated.
- When the network camera is online, you can double click camera name to edit it.

4. Select a network camera, and click Add to add it.

Add Network Camera Manually

Add the network cameras to your video recorder.

Before You Start

- Ensure your network camera is on the same network segment with that of your video recorder.
- Ensure the network connection is valid and correct.
- Ensure the network camera is activated.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click 🛨.

Add IP Camera (Custom)				×
Aud II Camera (Custolli)				~
O Refresh				
No. ≑	∣ Status	Protocol	∣ Managem	ent Port ∣ Devic
IP Camera Address				
IP Camera Address				
Channel No.				
Protocol	HIKVISION			
Management Port	8000			
Transfer Protocol	Auto			
User Name	admin			
Camera Password				
Use Camera Activation				
		Add More	Add	Cancel

Figure 6-10 Add IP Camera

3. Enter network camera parameters.

Use Camera Activation Password

If it is enabled, the video recorder will add the camera by the set channel default password. 4. Click **Add**.

Add Network Camera on Different Network Segment

If your network camera is on a different network segment, the device can search its IP address within a range of IP addresses, and add it.

Before You Start

- Ensure the network connection is valid and correct.
- Ensure the network camera password is the same as your video recorder.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click Advanced Search.
- 3. Enter Network Segment.




Figure 6-11 Enter Network Segment

4. Click Add.

Add Network Camera Through Plug-and-Play

If an inactive network camera or third party ONVIF camera is connected to your network, the video recorder may automatically detect and add the camera, or notify you to manually add it.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click More.
- 3. Select Plug-and-Play.
- 4. Optional: Enable **Auto Add Network Camera**. The video recorder would automatically detect and add the inactive network camera or third party ONVIF camera.




Figure 6-12 Auto Add Network Camera

iNote

If you turn off **Auto Add Network Camera**, when an inactive network camera or third party ONVIF camera is connected to your network, the video recorder would automatically detect it and notify you to add it.

Edit Network Camera

You can edit the IP address, protocol and other parameters of network cameras.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click 🧧 of an added network camera.

Channel Port

If the connected device is an encoding device with multiple channels, you can choose the channel to connect by selecting the channel port No. in the drop-down list.

- 3. Optional: Click **Edit IP** to edit camera IP addresses in batch. The system will allocate IP addresses to the selected cameras in order.
- 4. Click OK.

Upgrade Network Camera

The Network camera can be remotely upgraded through the device.

Before You Start

- Ensure you have inserted the USB flash drive to the device, and it contains the network camera upgrade firmware.
- Ensure your network camera is on the same network segment with your video recorder.
- Ensure the network connection is valid and correct.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click 🗘.
- 3. Click Yes to confirm.
- 4. Select the camera upgrade firmware from your storage device.
- 5. Click **Upgrade** to start upgrading. The camera will restarted automatically after upgrade completed.

Configure Advanced Camera Parameters

You can configure advanced camera parameters like camera IP address, camera password, etc.

Before You Start

- Ensure your network camera is on the same network segment with your video recorder.
- Ensure the network connection is valid and correct.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click 🙆.
- 3. Set camera parameters like IP address, camera password, etc.
- 4. Click **Apply**.

Import/Export IP Camera Configuration File

The information of added network camera can be generated into an excel file and exported to the local device for backup, including the IP address, port, password of admin, etc. And the exported file can be edited on your computer, like adding or deleting the content, and copy the setting to

other devices by importing the excel file to it.

Before You Start

Connect a backup device, such as a USB flash drive, to your video recorder.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click More.
- 3. Click **Export/Import** to export/import configuration files to the connected backup device.
- 4. Set the storage device and folder path.
- 5. Click Export/Import.

What to do next

After the importing process is completed, you must restart the video recorder.

Advanced Settings

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Camera**.
- 2. Click More.
- 3. Configure the parameters as your desire.

H.265 Auto Switch Configuration

If you enable the option, the device will automatically switch to H.265 stream for the network camera (which supports H.265 video format) for the initial access.

Upgrade

Upgrade the added network cameras.

Export/Import

The information of added network camera can be generated into an excel file and exported to the local device for backup, including the IP address, port, password of admin, etc. And the exported file can be edited on your computer, like adding or deleting the content, and copying the settings to other devices by importing the excel file to it.

Camera Activation Password Settings

Change the default password for activating and adding network cameras. For network cameras that are already connected, you can choose to change their passwords to this one in the following pup-up window.

Batch Configuration

The device can enable SVC function or automatically synchronize time of the selected network cameras.

Plug-and-Play

Enable **Auto Add Network Camera**on the Plug-and-Play page. The video recorder would automatically detect and add the inactive network camera or third party ONVIF camera.

6.3.3 Display Settings

Configure the OSD (On-Screen Display), image settings, exposure settings, day/night switch settings, etc.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Display**.
- 2. Set Camera.
- 3. Configure parameters as your desire.

OSD Settings

Configure the OSD (On-screen Display) settings for the camera, including date, time, camera name, etc.

Image Settings

Customize the image parameters including the brightness, contrast, and saturation for the live view and recording effect.

Exposure

Set the camera exposure time (1/10000 to 1 sec). A larger exposure value results in a brighter image.

Day/Night Switch

The camera can be set to day, night, auto or scheduled switch mode according to the surrounding illumination conditions or time schedule.

Backlight

Set the camera's wide dynamic range (0 to 100). When the surrounding illumination and the object have large differences in brightness, you should set the WDR value.

Image Enhancement

For optimized image contrast enhancement.

Camera Parameters Settings

You can configure the camera parameters, including day/night mode, supplement light mode, etc. For details, see *Configure Camera Parameters Settings* please.

Camera	[A1] Camera 01 ~			
Camera Name	Camera 01			
2-26-2023 ue 17124122		✓ OSD Settings		
		Display Name		
		Display Date		
		Display Week		
	KVISION	Date Format	MM-DD-YYYY	
		Time Format	24-hour	
	Camera 01	Display Mode	Non-Transparent & N	lot Fla 🗸
		OSD Font	32x32	
		> Image Settings		
Apply C	opy to			
		> Image Enhancement		
		> Camera Parameters Settir	ngs	

Figure 6-13 OSD

- 4. Drag the text frames on the preview window to adjust the OSD position.
- 5. Click Apply.

Configure Camera Parameters Settings

You can configure the camera parameters, including day/night mode, supplement light mode, etc.

Steps

- 1. Go to **Camera** \rightarrow **Display**.
- 2. Select a camera as your desire.
- 3. Edit name in Camera Name.
- 4. Configure the parameters.

Signal Switch

Switch the 4 MP or 5 MP signal from **Signal Switch**. 4 MP 25/30 fps and 5 MP 20 fps are selectable. The 4 MP 25 fps and 4 MP 30 fps signals are self-adaptive for the camera.

Enable Defog

Check **Enable Defog** to enable the defog function of the selected camera. And set the **Defog Level** from 1 to 4.

Day to Night Sensitivity/Night to Day Sensitivity

Adjust the parameters including **Day to Night Sensitivity**, **Night to Day Sensitivity** and **IR Light Brightness** for the cameras. The default value of **Day to Night Sensitivity**, **Night to Day Sensitivity** and **IR Light Brightness** is 5. The effective value ranges from 1 to 9

Day/Night Mode

Select **Day/Night Mode** of the camera from the drop-down list. As for the day mode, the image is always in color. As for the night mode, the image is black/white.

WDR Switch

Check **WDR Switch** to enable the function of the camera.

- 5. Optional: Click **Copy** to copy the parameters of the current camera to other cameras.
- 6. Optional: Click **Apply** to save the settings.

iNote

The parameters are saved to the connected camera and are not saved to the DVR.If you exit from the interface and enter it again, the parameters displayed are those you have set the last time.The camera parameters settings is only applicable for the cameras which support those functions.

6.3.4 Privacy Mask

You are allowed to configure the privacy mask areas that cannot be viewed or recorded.

Steps

- 1. Go to Configuration \rightarrow Camera \rightarrow Privacy Mask.
- 2. Select Camera.
- 3. Turn on **Enable**.



Figure 6-14 Privacy Mask

4. Drag to draw an area on the window. The frames of the areas will be marked with different colors.

iNote

Up to 4 privacy mask areas can be configured. The size of each area can be adjusted.

5. Click Apply.

6.4 Event Configuration

6.4.1 Multi-Capability Intelligence

When **Multi-Capability Intelligence Mode** is enabled, the device can run more than one smart function at the same time.

Before You Start

Ensure your device support this function.

Steps

1. Go to **Configuration** \rightarrow **Event** \rightarrow **Multi-Capability Intelligence**.

① Multi-Capability	Intelligence Mode 🦲		\geq				\sim $^{\prime}$	
③ Resource Pool	(Occupied/Total) 14.5	/16	م ال			1		
Channel	Motion Detection 2.0	Perimeter Prof	tection			Face Rec	ognition	AcuSearch
onanner	Motion Detection 2.0	Line Crossing	Intrusion	Region Er	ntrance Region Exiting	Face Cap	ture Face Picture Co	omparis
[A1] Caffffffhhf		8	8			8	8	8
[A2] Camera 02	•	0	8			8	8	0
[A3] Camera 03	8	8	8			0	8	8
[A4] Camera 04	8	8	8			8	8	8
[A5] Camera 05	8	8	8			8	8	8
[A6] Camera 06	8	8	8			0	8	8
[A7] Camera 07	0	8	8			8	8	8



- 2. Turn on Multi-Capability Intelligence Mode.
- 3. Optional: View the resource pool total resources and remaining resources. You can click **Resource Pool (Occupied/Total)** below the progress bar to view the resource consumption of each smart event.

Resource Pool (Occupi	ed(Total) 10/16
Event Resource Consum	ption Description
Smart Event	Resource Consumption per Channel
Motion Detection 2.0	0.5
Perimeter Protection	2
Face Recognition	4
AcuSearch	2

Figure 6-16 Resource Consumption of Each Smart Event

- 4. Move the cursor on the table, and select a position as your desire according to the channel and event type.
- 5. Click **Configuration** of the select channel and event type.

Channel	Motion Detection 2.0	Perimeter Prot	ection			Face Recognit	ion	AcuSearch
JIIIIII	Motion Detection 2.0	Line Crossing	Intrusion	Region Entrance	Region Exiting	Face Capture	Face Picture Comparis	
[A1] Caffffffhhf	8	The event is	not enabled	-		8	8	8
[A2] Camera 02	8	Configuration	on			8	0	0
[A3] Camera 03	0	8	8			8	0	8
[A4] Camera 04	8	8	8			8	8	8
[A5] Camera 05	0	8	8			8	0	8
[A6] Camera 06	8	8	8			0	•	8
[A7] Camera 07	0	8	8			8	•	8
[A8] Camera 08	8	8	8			0	•	8
[A9] Camera 09	8	8	8			8	0	8
[A10] Camera 10	0	8	8			8	0	8

Figure 6-17 Select Event and Channel

6. Configure the corresponding event. For configuration details, please refer to other sections at this chapter.

iNote

If there is not enough resource, in order to release resource, the system will notify you to disable a part of other events.

Enabling Failed			×
	source: 0. Enabling the event t of the following events to re		nel will cost 0.5.
Camera	Enabled Event(s)	Resource	l Enable
[A1] Caffffffhhfv	Face Recognition	4	
[A2] Camera 02	AcuSearch	2	
[A3] Camera 03	Motion Detection 2.0	0.5	
[A4] Camera 04	Motion Detection 2.0	0.5	
[A5] Camera 05	Motion Detection 2.0	0.5	
[A6] Camera 06	Face Recognition	4	
[A7] Camera 07	Motion Detection 2.0	0.5	
[A8] Camera 08	Face Recognition	4	-
ng mining sa			
			Cancel

Figure 6-18 Release System Resource

6.4.2 Normal Event

Motion Detection

Motion Detection enables the video recorder to detect the moving objects in the monitored area

and trigger alarms.

Steps

- 1. Go to **Configuration** \rightarrow **Camera** \rightarrow **Motion Detection**.
- 2. Select a camera.
- 3. Check Enable.
- 4. Set the motion area: Click Draw Area or Clear to draw or clear areas.

iNote

The operation may differ according to different models.

- 5. Adjust **Sensitivity**. Sensitivity allows you to calibrate how readily movement triggers the alarm. A higher value results in the more readily to triggers motion.
- 6. Set analysis mode as **AI** or **PIR**.

AI

The motion event will be analyzed by your device.

PIR

The motion event will be analyzed by certain analog PIR cameras.

- 7. Optional: Set **Detection Target** as **Human** or **Vehicle** to discard alarms which are not triggered by human or vehicle.
- 8. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 9. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 10. Click Apply.

Video Tampering

Trigger alarm when the lens is covered and take alarm response actions.

Steps

1. Go to Configuration \rightarrow Event \rightarrow Normal Event \rightarrow Video Tampering.

Camera [D8] Can Enable ()	nera 01 🗸		
Area Arming Schedule Linl	kage Action		
04-27-2020 Non 01:17:31		Sensitivity <u> </u> 1	
	Cancra 01		
Clear			

Figure 6-19 Video Tampering

- 2. Set Camera.
- 3. Turn on **Enable**.
- 4. Adjust **Sensitivity** as your desire. The higher the value is, the more easily the video tampering can be triggered.
- 5. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 6. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 7. Click Apply.

Video Loss

Detect video loss of a camera and take alarm response actions.

Steps

- 1. Go to Configuration \rightarrow Event \rightarrow Normal Event \rightarrow Video Loss.
- 2. Set Camera.
- 3. Turn on **Enable**.
- 4. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 5. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 6. Click **Apply**.

Alarm Input

Set linkage actions for an external sensor alarm.

Steps

1. Go to Configuration \rightarrow Event \rightarrow Normal Event \rightarrow Alarm Input.

Digital Video Recorder User Manual

Alarm Input No.	I Alarm Name	∣ Alarm Type	Enable	Operation
Local<-1		N.O	No	L
Local<-2		N.O	No	L
Local<-3		N.O	No	L
Local<-4		N.O	No	L

Figure 6-20 Alarm Input

iNote

Local alarm input: Local alarm input is triggered by the external device that connected to the video recorder's terminal block.

2. Click 🦉 of a desired alarm input.

Alarm Input No.	Local<-1		~	Туре	N.O	~
Alarm Name						
Settings 🤇	Nonuse	O Input	O One-Key Disarmin	ıg		

Figure 6-21 Edit Alarm Input

- 3. Customize Alarm Name.
- 4. Set alarm type as N.O (normally open) or N.C (normally closed).
- 5. Set **Settings** as **Input** to enable the function.

iNote

If you set **Settings** as **Nonuse**, the alarm input will be disabled. If you set **Settings** as **One-Key Disarming**, the selected linkage method(s) of the alarm input will be disabled.

- 6. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 7. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 8. Click Apply.

Alarm Output

Trigger an alarm output when an alarm is triggered.

Steps

1. Go to Configuration \rightarrow Event \rightarrow Normal Event \rightarrow Alarm Output.




Figure 6-22 Alarm Output

- 2. Click 🖉 of a desired alarm output.
- 3. Customize Alarm Name.
- 4. Select **Dwell Time**.



Figure 6-23 Edit Alarm Output

- 5. Set **Settings** as **Input** to enable the function.
- 6. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 7. Click Apply.

Exception

Exception events can be configured to take the event hint in the live view window and trigger alarm outputs and linkage actions.

Steps

- 1. Go to Configuration \rightarrow Event \rightarrow Normal Event \rightarrow Exception.
- 2. Configure event hint. When the set events occur, you will receive hints in alarm center.
 - 1) Enable Event Hint.
 - 2) Select events to hint. Choose from:
 - Click 🚳 of Set Event Hint to select events.
 - Click 📮 in the upper-right corner of local menu to enter alarm center to select events.
- 3. Select Exception Type to set its linkage actions.

Digital Video Recorder User Manual

	© 命 HDD Full	~
□ Normal Linkage		Trigger Alarm Output
Buzzer Alarm		□Local->1
□ Notify Surveillance Center		
☐ Send Email		
Apply		

Figure 6-24 Exceptions

- 4. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 5. Click Apply.

Flashing Light Alarm Output

When light and audio alarm camera is connected, you can set the flashing time, flashing frequency, and arming schedule of the flashing light alarm.

Before You Start

Light and audio alarm camera is connected.

Steps

- 1. Go to Configuration \rightarrow Event \rightarrow Normal Event \rightarrow Flashing Light Alarm Output.
- 2. Click 🖉 for any row.
- 3. Set the Flashing Time and Flashing Frequency.
- 4. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 5. Click**Save**.

Audio Alarm Output

When light and audio alarm camera is connected, you can set the parameters and arming schedule of the audio alarm.

Before You Start

Light and audio alarm camera is connected.

Steps

- 1. Go to Configuration \rightarrow Event \rightarrow Normal Event \rightarrow Flashing Light Alarm Output.
- 2. Click 🖉 for any row.
- 3. Select the Audio Type as Alarm Sound, Prompt Sound, or Custom Audio.

iNote

When you select the **Alarm Sound**, you also need to select the alarm sound type. When you select the **Alarm Sound**, you also need to upload the custom audio, enter the audio name and select the uploaded audio in the drop-down box of **Custom Audio**.

4. Set the Alarm Times and Sound Volume.

- 5. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 6. Click**Save**.

6.4.3 Perimeter Protection

Perimeter protection includes line crossing detection, intrusion detection, region entrance detection, and region exiting detection.

iNote

Perimeter protection is only available for certain device models or camera models.

Line Crossing Detection

Line crossing detection detects people, vehicles, and objects crossing a set virtual line. The detection direction can be set as bidirectional, from left to right or from right to left.

Steps

- 1. Go to **Configuration** \rightarrow **Event** \rightarrow **Perimeter Protection** \rightarrow **Line Crossing**.
- 2. Set Camera.
- 3. Turn on **Enable**.
- 4. Set the detection rules and detection areas.
 - 1) Set Arming Area.
 - 2) Set Direction as A<->B, A->B, or A<-B.

A<->B

Only the arrow on the B side shows. An object crossing a configured line in both directions can be detected and trigger alarms.

A->B

Only an object crossing the configured line from the A side to the B side can be detected.

B->A

Only an object crossing the configured line from the B side to the A side can be detected.

- 3) Click **Max. Size** and draw a quadrilateral in the preview window to set the maximum draw area size of the target.
- 4) Click **Min. Size** and draw a quadrilateral in the preview window to set the minimum draw area size of the target.
- 5) Click **Draw Area** and draw a quadrilateral in the preview window by specifying four vertexes of the detection region.
- 5. Adjust **Sensitivity**. Sensitivity allows you to calibrate how readily movement triggers the alarm. A higher value results in the more readily to triggers motion detection.
- 6. Optional: Set **Detection Target** as **Human** or **Vehicle** to discard alarms which are not triggered by human or vehicle.

iNote

This function is only available for certain models.

- 7. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 8. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 9. Click **Apply**.

Intrusion Detection

Intrusion detection function detects people, vehicles, or objects that enter and loiter in a predefined virtual region.

Steps

- 1. Go to **Configuration** \rightarrow **Event** \rightarrow **Perimeter Protection** \rightarrow **Intrusion**.
- 2. Select Camera to configure.
- 3. Turn on Enable.
- 4. Set the detection rules and detection areas.
 - 1) Select Arming Area.
 - 2) Adjust Time Threshold and Sensitivity.

Sensitivity

The size of the object that can trigger the alarm. The higher the value is, the more easily the detection alarm will be triggered. Its range is [1-100].

Time Threshold

Range [1s-10s], the threshold for the time of the object loitering in the region. When the duration of the object in the defined detection area is longer than the set time, the alarm will be triggered.

3) Optional: Set **Detection Target** as **Human** or **Vehicle** to discard alarms which are not triggered by human body or vehicle.

iNote

This function is only available for certain models.

- 4) Click **Max. Size** and draw a quadrilateral in the preview window to set the maximum draw area size of the target.
- 5) Click **Min. Size** and draw a quadrilateral in the preview window to set the minimum draw area size of the target.
- 6) Click **Draw Area** and draw a quadrilateral in the preview window by specifying four vertexes of the detection region.
- 5. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 6. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 7. Click **Apply**.

Region Entrance Detection

Region entrance detection function detects people, vehicles or other objects which enter a predefined virtual region from the outside place, and some certain actions can be taken when the alarm is triggered.

Steps

- 1. Go to **Configuration** \rightarrow **Event** \rightarrow **Smart Event** \rightarrow **Region Entrance**.
- 2. Set Camera.
- 3. Select VCA Mode.

By NVR

The event will be analyzed by NVR. The device can analyze videos that contain human and vehicle. Only the target of selected type (human or vehicle) will trigger alarms, which can reduce false alarms that are caused by other objects.

By Camera

The event will be analyzed by camera.

- 4. Optional: Check **Learn-by-Example Mode** to enable self-learning function. The device will analyze this event for a second time to reduce false alarms. Refer to for details.
- 5. Turn on **Enable**.
- 6. Optional: Check Save VCA Picture to save the captured pictures of VCA detection.
- 7. Set the detection rules and detection areas.
 - 1) Set **Arming Area**. Up to 4 arming areas are selectable.
 - 2) Adjust **Sensitivity**. **Sensitivity**: Range [0-100]. The higher the value is, the more easily the detection alarm can be triggered.
 - 3) Optional: Set **Detection Target** as **Human** or **Vehicle** to discard alarms which are not triggered by human body or vehicle.
 - 4) Click **Max. Size** and draw a quadrilateral in the preview window to set the maximum draw area size.
 - 5) Click **Min. Size** and draw a quadrilateral in the preview window to set the minimum draw area size.
 - 6) Click **Draw Area** and draw a quadrilateral in the preview window by specifying four vertexes of the detection region.
- 8. Set the arming schedule. Refer to *Configure Arming Schedule* for details.

9. Set the linkage actions. Refer to <u>Configure Alarm Linkage Action</u> for details.
 10. Click **Apply**.

Region Exiting Detection

Region exiting detection function detects people, vehicles or other objects which exit from a predefined virtual region, and some certain actions can be taken when the alarm is triggered.

Steps

- 1. Go to **Configuration** \rightarrow **Event** \rightarrow **Smart Event** \rightarrow **Region Exiting**.
- 2. Set **Camera**.
- 3. Select VCA Mode.

By NVR

The event will be analyzed by NVR. The device can analyze videos that contain human and vehicle. Only the target of selected type (human or vehicle) will trigger alarms, which can reduce false alarms that are caused by other objects.

By Camera

The event will be analyzed by camera.

- 4. Optional: Check **Learn-by-Example Mode** to enable self-learning function. The device will analyze this event for a second time to reduce false alarms. Refer to for details.
- 5. Turn on **Enable**.
- 6. Optional: Check Save VCA Picture to save the captured pictures of VCA detection.
- 7. Set the detection rules and detection areas.
 - 1) Set Arming Area. Up to 4 arming areas are selectable.
 - 2) Adjust **Sensitivity**. **Sensitivity**: Range [0-100]. The higher the value is, the more easily the detection alarm can be triggered.
 - 3) Optional: Set **Detection Target** as **Human** or **Vehicle** to discard alarms which are not triggered by human body or vehicle.
 - 4) Click **Max. Size** and draw a quadrilateral in the preview window to set the maximum draw area size.
 - 5) Click **Min. Size** and draw a quadrilateral in the preview window to set the minimum draw area size.
 - 6) Click **Draw Area** and draw a quadrilateral in the preview window by specifying four vertexes of the detection region.
- 8. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 9. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 10. Click **Apply**.

6.4.4 Face Recognition

Face recognition is the function that compares a captured face (in image or video stream) with those in face picture libraries and returns its identity information if the face is recognized. Based on facial feature of human being, face recognition first checks if human face exists in the input

image or video stream. If there is a human face, the function compares the face data (such as position, size, and facial feature) with those in current face picture libraries to identify the person.

Before You Start

Make sure you have configured related parameters on Hik Central Professional or Hik Connect and disabled **Motion Detection** and **Perimeter Protection**.

iNote

This function is only available for certain models.

Face Capture

Face capture detects human faces appearing in the scene. Linkage actions can be triggered when a human face is detected.

Steps

1. Go to Configuration \rightarrow Event \rightarrow Face Recognition \rightarrow Face Capture.

	E	Enable 🤇			Sensitivity		•	3					
	Schedule		ge Action										
Arm	🔶 Clear										∠ Edit	🗇 Clea	ar All
		2	4	6	8	10	12	14	16	18	20	22	24
Mon										_			
Tue													
Wed													
Thu													
Fri													
Sat	_												
Sun													-
-	-												
Арр	oły												

Figure 6-25 Face Capture

- 2. Select Camera.
- 3. Turn on **Enable**.
- 4. Adjust Sensitivity.

Sensitivity

The higher the value is, the more easily the defocus image can trigger the alarm.

- 5. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 6. Set the linkage actions. Refer to *Configure Alarm Linkage Action* for details.
- 7. Click **Apply**.

Face Picture Comparison

Face picture comparison compares the detected face pictures with face pictures in the face picture library. The device will trigger an alarm when comparison succeeded.

Before You Start

Ensure you have created at least one face picture library, and face pictures are added to the library. Refer to *Face Picture Library Management* for operation details.

Steps

1. Go to Configuration \rightarrow Face Recognition \rightarrow Face Picture Comparison.

	Enab	ole 🧾		
List Lil	orary Linkage	Arming Schedule	Linkage Succeeded	Linkage Failed
	Library Nan	ne	Similarity	
	sr			
			75	

Figure 6-26 Face Picture Comparison

- 2. Select a camera.
- 3. Turn on Enable.
- 4. Select the face picture library (or libraries) in List Library Linkage.
- 5. Set the face picture library similarity.

Similarity

Similarity value ranges from 0 to 100. Device will analyze the similarity between the detected face picture and face pictures in the library. When the similarity reaches the threshold value, the face picture comparison succeeded, and the face picture is recognized.

- 6. Set the arming schedule. Refer to *Configure Arming Schedule* for details.
- 7. Set the linkage actions for Linkage Succeeded and Linkage Failed. Refer to <u>Configure Alarm</u> <u>Linkage Action</u> for details.

Linkage Succeeded

The device will perform linkage actions when the face picture comparison succeeded.

Linkage Failed

The device will perform linkage actions when the face picture comparison failed.

8. Click Apply.

6.4.5 Configure Arming Schedule

Steps

- 1. Click Arming Schedule.
- 2. Choose one day of a week and set the time segment. Up to eight time periods can be set within each day.

iNote

Time periods shall not be repeated or overlapped.




Figure 6-27 Set Arming Schedule

3. Click **Apply**.

6.4.6 Configure Alarm Linkage Action

Configure Alarm Pop-up Window

When an alarm is triggered, the local monitor displays in full screen the video image from the alarming channel configured for full screen monitoring. And when the alarm is triggered simultaneously in several channels, you must configure the auto-switch dwell time.

Steps

- 1. Go to **Configuration** \rightarrow **System** \rightarrow **Live View** \rightarrow **General**.
- 2. Set the event output and dwell time.

Alarm Pop-up Output

Select the output to show event video.

Alarm Pop-up Delay

Set the time in seconds to show alarm event image. If alarms are triggered simultaneously in

several channels, their full-screen images will be switched at an interval of 10 seconds (default dwell time).

- 3. Click Linkage Action of the alarm detection.
- 4. Select Alarm Pop-up Window alarm linkage action.
- 5. Select the channel(s) in Trigger Channel settings you want to make full screen monitoring.

iNote

Auto-switch will terminate once the alarm stops and back to the live view interface.

Configure Buzzer Alarm

The audio warning enables the video recorder to trigger an audible beep when an alarm is detected.

Steps

- 1. Go to **Configuration** \rightarrow **System** \rightarrow **Live View** \rightarrow **General**.
- 2. Turn on Audio, and set Volume.
- 3. Go to Linkage Action interface of the alarm detection.
- 4. Select **Buzzer Alarm** linkage action.

Notify Surveillance Center

The video recorder can send an exception or alarm signal to the remote alarm host when an event occurs. The alarm host refers to the computer installed with client software (e.g., iVMS-4200, iVMS-5200).

Steps

- 1. Go to **Configuration** \rightarrow **Network** \rightarrow **General** \rightarrow **More Settings**.
- 2. Set Alarm Host IP and Alarm Host Port.
- 3. Go to Linkage Action interface of the alarm detection.
- 4. Select Notify Surveillance Center.

Configure Email Linkage

The video recorder can send an email with alarm information to a user or users when an alarm is detected.

Steps

- 1. Go to **Configuration** \rightarrow **Network** \rightarrow **Email**.
- 2. Configure the settings.
- 3. Go to Linkage Action interface of the alarm detection.
- 4. Select Send Email as alarm linkage action.

Trigger Alarm Output

The alarm output can be triggered by the normal and smart events.

Steps

- 1. Go to Linkage Action interface of the alarm input or event detection.
- 2. Click Alarm Output Linkage.
- 3. Select the alarm outputs to trigger.
- 4. Go to Configuration \rightarrow Event \rightarrow Normal Event \rightarrow Alarm Output.
- 5. Select an alarm output item from the list. Refer to <u>Alarm Output</u> for details.

Configure PTZ Linkage

Video recorder can trigger the PTZ actions (e.g., call preset/patrol/pattern) when the alarm event, or VCA detection events occur.

Steps

- 1. Go to Linkage Action interface of the alarm input or VCA detection.
- 2. Select PTZ Linkage.
- 3. Select the camera to perform the PTZ actions.
- 4. Select the preset/patrol/pattern No. to call when the alarm events occur.

PTZ Linkage						
Linkage Channel	[D1]					
Preset No.	1 ~					
O Patrol No.	1					
O Pattern No.	1					

Figure 6-28 PTZ Linkage

iNote

You can set one PTZ type only for the linkage action each time.

6.5 Intelligent Search

6.5.1 AcuSearch

Enable AcuSearch function for selected channels.

Steps

- 1. Go to Configuration \rightarrow Intelligent Search \rightarrow Acu Search.
- 2. Turn on Enable.
- 3. Select the channels on which you want to enable the AcuSearch function.
- 4. Click **Apply**.

iNote

You can perform AcuSearch in playback interface. For details, please refer to *Normal Playback* and *Slice Playback*.

6.6 Recording Management

6.6.1 Configure Recording Schedule

Video recorder will automatically start/stop recording according to the configured schedule.

Configure Continuous Recording

Steps

- 1. Go to **Configuration** \rightarrow **Record** \rightarrow **Parameter**.
- 2. Set the continuous main stream/sub-stream recording parameters for the camera.
- 3. Go to **Configuration** \rightarrow **Record** \rightarrow **Schedule**.
- 4. Select recording type as **Continuous**.

Configure Event Recording

You can configure the recording triggered by the line crossing detection, intrusion detection, etc..

Steps

- 1. Go to **Configuration** \rightarrow **Event**.
- 2. Configure the event detection and select the cameras to trigger the recording when event occurs.
- 3. Go to **Configuration** \rightarrow **Record** \rightarrow **Parameter**.
- 4. Set the continuous main stream/sub-stream recording parameters for the camera.

- 5. Go to **Configuration** \rightarrow **Record** \rightarrow **Schedule**.
- 6. Select recording type as **Event**.

Edit Schedule

Steps

1. Go to **Configuration** \rightarrow **Record** \rightarrow **Schedule**.




Figure 6-29 Recording Schedule

Continuous

Continuous recording.

Event

Recording triggered by all event triggered alarms.

- 2. Select a camera in Camera No.
- 3. Turn on **Enable**.
- 4. Configure the recording schedule.
 - 1) Click Edit.
 - 2) Select a day to configure in Weekday.
 - 3) To set an all-day recording schedule, check **All Day** and select schedule **Type**.
 - 4) To set other schedules, uncheck All Day and set Start/End time and schedule Type.

iNote

Up to 8 periods can be configured for each day. And the time periods cannot be overlapped with each other.

5) Click **OK** to save the settings and go back to upper level menu.

iNote

You can also select schedule type as **Continuous** or **Event**, and drag the cursor on the desired period to draw a colored bar.

5. Click Advanced to set advanced parameters.

Record Audio

Audio will be record to the video file.

Pre-Record

The time you set to record before the scheduled time or event. For example, when an alarm triggers the recording at 10:00, and if you set the pre-record time as 5 seconds, the camera records at 9:59:55.

Post-Record

The time you set to record after the event or the scheduled time. For example, when an alarm triggered recording ends at 11:00, and if you set the post-record time as 5 seconds, it records till 11:00:05.

Stream Type

Main stream and sub-stream are selectable for recording. When you select sub-stream, you can record for a longer time with the same storage space.

Video/Picture Expiry Time

The expiry time is period for a recorded file to be kept in the HDD. When the deadline is reached, the file will be deleted. If you set the expiry time to 0, the file will not be deleted. The actual keeping time for the file should be determined by the capacity of the HDD.

- 6. Click **OK** to save the advanced settings.
- 7. Click Apply.

6.6.2 Configure Recording Parameter

Steps

- 1. Go to **Configuration** → **Record** → **Parameter** to configure camera main stream and sub-stream parameters.
- 2. Configure recording parameters.

Main Stream

Main stream refers to the primary stream that affects data recorded to the hard disk drive and will directly determine your video quality and image size. Comparing with the substream, the main stream provides a higher quality video with higher resolution and frame rate.

Main Stream (Continuous) refers to the main stream of normal recording. Main Stream (Event) refers to the main stream of event recording.

Sub-Stream

Sub-stream is a second codec that runs alongside the mainstream. It allows you to reduce the outgoing internet bandwidth without sacrificing your direct recording quality. Sub-stream is often exclusively used by smartphone applications to view live video. Users with limited internet speeds may benefit most from this setting.

Stream Type

You can choose to include video and audio or only video in the recording.

Resolution

Image resolution is a measure of how much detail a digital image can hold: the greater the resolution, the greater the level of detail. Resolution can be specified as the number of pixel-columns (width) by the number of pixel-rows (height), for example, 1024 × 768.

Bitrate Type

Variable bitrate: The bitrate would be adjusted based on different scenarios, which leads to higher utilization of network bandwidth, thus saving storage space. You can set 6 levels of **Video Quality**. If you select **H.265** as **Video Encoding** format, the system will adopt H.265 Pro encoding.Constant bitrate: Encode at the maximum bitrate. **Video Quality** is not adjustable.

Frame Rate

Frame rate refers to how many frames are captured each second. A higher frame rate is advantageous when there is movement in the video stream, as it maintains image quality throughout.

Max. Bitrate Mode

General: Fixed-value parameters are available for selection. **Custom**: Customize the value of the maximum bitrate.

Video Encoding

Select the video encoding format. The options are determined by the connected camera.

Enable H.265+

The H.265+ mode helps to ensure the high video quality with a lowered bitrate. It can effectively reduce the need of bandwidth and HDD storage space.

3. Click Apply.

6.6.3 Storage Device

Initialize HDD

If it is the first time you use your HDD, please initialize it after it is installed.

Before You Start

Install at least an HDD to your video recorder.

Steps

- 1. Go to **Configuration** \rightarrow **Record** \rightarrow **Storage**.
- 2. Select an HDD.
- 3. Click Init.

Repair Database

Repair an HDD that with error in database. Please operate it with the help of professional technical support.

Add Network Disk

You can add the allocated NAS or IP SAN disk to the video recorder, and use it as a network HDD.

Steps

- 1. Go to **Configuration** \rightarrow **Record** \rightarrow **Storage**.
- 2. Click Add.
- 3. Set NetHDD.
- 4. Set Type as NAS or IP SAN.
- 5. Enter NetHDD IP address.
- 6. Click **Q** to search the available disks.

Custom Add				×
	NetHDD	NetHDD 1	~	
	Туре	NAS	~	
	NetHDD IP			
NetH	DD Directory			Q
No.	Directory			
-				
			Cancel	

Figure 6-30 Add NetHDD

7. Select NAS disk from the list, or manually enter the directory in **NetHDD Directory**.

8. Click **OK**.

iNote

Up to 8 TB storage capacity is allowed for each network disk.

Result

The added network disks will be displayed in the storage device list.

6.6.4 Configure Storage Mode

Configure HDD Quota

Each camera can be configured with an allocated quota for storing videos.

Steps

iNote

This function is only available for certain models.


1. Go to Configuration \rightarrow Record \rightarrow Storage Mode.

2. Set Mode as Quota.

3. Select a camera to set quota in Camera.

4. Enter the storage capacity in **Record Capacity**.

Mode	Quota	O Group
Camera	[D1] IPCamera 01	
Used Record Capacity	31.00GB	
HDD Capacity	1863GB	
Record Capacity (GB)	0	
A	Free quota space: 1863	GB, used picture space: 15.00GB.
	Apply Co	ру



_____ INote

When the quota capacity is set to 0, all cameras will use the total capacity of HDD for videos and pictures.

5. Click Apply.

6. Restart the video recorder to activate the new settings.

Configure HDD Groups

Multiple HDDs can be managed in groups. Video from specified channels can be recorded onto a particular HDD group through HDD settings.

Steps

iNote

This function is only available for certain models.

1. Go to Configuration \rightarrow Record \rightarrow Storage Mode.

- 2. Select Mode as Group.
- 3. Select a group number.
- 4. Select IP cameras to record on the HDD group.

Record on HDD	Mode O C	Quota	 Group ✓ 	p				
☑ IP Camera	☑ D1 ☑ D9	☑ D2 ☑ D10	☑ D3 ☑ D11	☑ D4 ☑ D12	☑ D5 ☑ D13	☑ D6 ☑ D14	☑ D7 ☑ D15	☑ D8 ☑ D16
Apply								

Figure 6-32 Group

- 5. Click **Apply**.
- 6. Restart the video recorder to activate the new storage mode settings.
- 7. After restart, go to **Configuration** \rightarrow **Record** \rightarrow **Storage**.
- 8. Click 🖉 of desired HDD to set the group.
- 9. Select a group number for the current HDD.
- 10. Click **Apply**.

iNote

Regroup the cameras for HDD if the HDD group number is changed.

6.6.5 Advanced Settings

Steps

- 1. Go to **Configuration** \rightarrow **Record** \rightarrow **Advanced**.
- 2. Configure the parameters as your desire.

Overwrite

- Disable: When the HDD is full, video recorder will stop writing.
- Enable: When hard drive is full, video record will continue to write new files by deleting the oldest files.

HDD Sleeping

HDDs which are free of working for a long time will turn into sleep status.

Save Camera VCA Data

Camera VCA data will be saved so that you can search it.

iNote

Disabling **Save Camera VCA Data** will delete the existing Dual-VCA and motion detection information, and stop analyzing and storing Dual-VCA and motion detection information.

Alarm Storage

When the HDD free space is not enough, you can disable it to save space, but your device will

stop storing alarm information.

Picture Storage

When the HDD free space is not enough, you can disable it to save space, but your device will stop storing pictures.

6.7 Face Picture Library Management

Face picture library is mainly used for face picture storage and face picture comparison.

iNote

The section is only available for certain models.

6.7.1 Add a Face Picture Library

Face picture library is used to store face pictures, it is essential for face picture comparison.

Steps

- 1. Go to **Configuration** \rightarrow Face Picture Library.
- 2. Enter the admin password for authorization.
- 3. Click Add.
- 4. Enter the face picture library name.
- 5. Click Add.

iNote

You can also go to **Search** \rightarrow **Human** to add the search results to the **Face Picture Library**.

What to do next

After a face picture library is added, you can edit its name, delete it, or upload face pictures to it.

6.7.2 Upload Face Pictures to the Library

You can upload a single face picture or import multiple face pictures to the library.

Before You Start

Ensure you have created a face picture library and enabled face picture comparison.

Steps

1. Go to Configuration \rightarrow Face Picture Library.

- 2. Find the face picture library that you are going to upload face pictures, and click <a>[@].
- 3. Click Add.
- 4. Import picture(s).



Add one face picture to the library.

Add multiple face pictures to the library.

iNote

- Only JPG and JPEG formats are supported.
- Each picture size should be less than 1 MB.
- The picture resolution shall be between 80 × 80 and 1920 × 1080.
- Only the pictures in the USB flash drive can be imported.

Chapter 7 Maintenance

7.1 Restore Default

Steps

- 1. Click 🔘 at the upper-right corner.
- 2. Select the restoring type.

Simple Restore

Restore all parameters, except the network (including IP address, subnet mask, gateway, MTU, NIC working mode, default route, server port, etc.) and user account parameters, to the factory default settings.

Factory Defaults

Restore all parameters to the factory default settings.

Restore to Inactive

Restore the device to the inactive status, and leave all settings unchanged except restoring user accounts.

3. Click **Yes**. The device will reboot automatically.

7.2 Search Log

The operation, alarm, exception and information of video recorder can be stored in logs, which can be viewed and exported at any time.

Steps

- 1. Click 🔟 at the upper-right corner.
- 2. Click More.
- 3. Click Log Information.
- 4. Set the search conditions.
- 5. Click Search.

7.3 System Service

- 1. Click 🔟 at the upper-right corner.
- 2. Click More.
- 3. Click System Service.

4. Configure the parameters as your desire.

RTSP

You can specifically secure the stream data of live view by setting the RTSP authentication.

RTSP Authentication

Two authentication types are selectable, if you select **digest**, only the request with digest authentication can access the video stream by the RTSP protocol via the IP address. For security reasons, it is recommended to select **digest** as the authentication type.

ISAPI

ISAPI (Internet Server Application Programming Interface) is an open protocol based on HTTP, which can realize the communication between the system devices (e.g., network camera, NVR, etc.). The video recorder is used as a server, the system can find and connect the video recorder.

HTTP

The admin user account can disable the HTTP service from the GUI or the web browser. After the HTTP is disabled, all the related services, including ISAPI and ONVIF, will terminate as well.

HTTP Authentication

If you need to enable the HTTP service, you can set the HTTP authentication to enhance the access security. Two authentication types are selectable. For security reasons, it is recommended to select **digest** as the authentication type.

Camera Added Detection

The function detects the network camera status. If the network camera has been added by another video recorder, the network camera status will show as A in **Online Device** list.

5. Click Apply.

7.4 Buzzer Switch

You can enable or disable buzzer with alarm linkage or exceptional linkage.

- 1. Click 🔘 at the upper-right corner.
- 2. Click More.
- 3. Go to Buzzer Switch.
- 4. Turn on or turn off **Enable**.

7.5 Device Maintenance

7.5.1 Schedule Reboot

The device will automatically restart according to the schedule.

Steps

- 1. Click 🔘 at the upper-right corner.
- 2. Click More.
- 3. Go to **Device Maintenance** \rightarrow **Enable Schedule Reboot**.
- 4. Turn on **Enable**.
- 5. Set the reboot schedule.
- 6. Click **Apply**.

7.5.2 Device Status

You can mute the selected channel(s).

Steps

- 1. Click 🔘 at the upper-right corner.
- 2. Click More.
- 3. Go to **Device Maintenance** \rightarrow **Device Status**.
- 4. In the **Mute and Not Disturb** column, check the corresponding channel(s).

Result

The selected channel(s) will be muted.

7.5.3 Time Sync Diagnosis

View time sync information and enable time sync exception detection.

Steps

- 1. Click 🔟 at the upper-right corner.
- 2. Click More.
- 3. Go to **Device Maintenance** → **Time Sync Diagnosis**. View the current time sync information.
- 4. Click **Time Sync Configuration**.
- 5. Turn on Enable Time Sync Exception Detection.

iNote

Supports detection of multiple time sync sources. If multiple time sync sources are detected, you need to turn off unnecessary time sync sources in time, otherwise it may cause device time changes, which will affect the recording. Supports RTC battery detection. If RTC battery is running

out, device time exception will occur, which may cause video loss or incorrect recording time. Please change the button cell battery on the mainboard and sync time again.

6. Click OK.

7.6 Upgrade

Warning

Do not shutdown or turn off the power during upgrade.

7.6.1 Local Upgrade

Before You Start

Store the upgrade firmware to a backup device, and connect it to your device.

Steps

- 1. Click 🔘 at the upper-right corner.
- 2. Click 0.
- 3. Click Local Upgrade.
- 4. Select a backup device in **Device Name**.
- 5. Select the upgrade firmware.
- 6. Click **Upgrade**. Your device will reboot automatically.

7.6.2 Online Upgrade

Upgrade the device with the latest online firmware.

Before You Start

Ensure Hik-Connect is enabled and properly configured. Refer to *<u>Hik-Connect</u>* for details.

Steps

- 1. Click 🔘 at the upper-right corner.
- 2. Click 🗿.
- 3. Go to Online Upgrade.
- 4. Download the latest firmware.
 - Auto Download It will automatically check and download the latest firmware.

Test Upgrade	Click Test Upgrade to manually check and download the latest
	firmware.

5. Upgrade your device if a new firmware version is available. The device will reboot automatically.

Chapter 8 Alarm

When events occur, you can view their details in alarm center.

8.1 Set Event Hint

Select the events to hint in alarm center.

Steps

- 1. Click 🚇 at the upper-right corner.
- 2. Select event type as your desire.
- 3. Click 🔯 and select events to hint.
- 4. Click OK.

When the selected events occur, the alarm information will be displayed in [4] (locating at the upper-right corner of local menu).

8.2 View Alarm in Alarm Center

- 1. Click 🚇 at the upper-right corner of local menu.
- 2. Select event type to view as your desire.

Chapter 9 Web Operation

9.1 Introduction

You can get access to the video recorder via web browser.

You may use one of the following listed web browsers: Internet Explorer 11.0, Apple Safari, Mozilla Firefox, and Google Chrome. The supported resolutions include 1024×768 and above.

For certain models, you will have to download a web component plug-in, and install it. Otherwise, a few functions would be unavailable. The download address is <u>http://hikdownload.ys7.com/web/webplugin/windows/WebComponents/standard/WebComponents.exe</u>.

9.2 Login

You shall acknowledge that the use of the product with Internet access might be under network security risks. For avoidance of any network attacks and information leakage, please strengthen your own protection. If the product does not work properly, please contact with your dealer or the nearest service center.

Steps

1. Open web browser, input the IP address of the video recorder and then press Enter.

iNote

If you have changed HTTP port, enter *http://IP address:HTTP port* in address bar. E.g., *http: 192.168.1.64:81*.

2. Enter user name and password in the login interface.

3. Click Login.

👤 admin	
	••••
	Login

Figure 9-1 Login

4. Follow the installation prompts to install the plug-in.

iNote

You may have to close the web browser to finish the installation of the plug-in.


9.3 Live View

After login, live view interface shows.



Figure 9-2 Live View

9.4 Playback



Click **Playback** to enter playback interface.

Figure 9-3 Playback

9.5 Configuration


Q	Local	Live View Parameters				
	System	Protocol	TCP		MULTICAST	
\mathbf{O}	Network	Stream Type	Main Stream	⊖ Sub-stream		
Q.	Video/Audio	Play Performance	 Shortest Delay 	 Balanced 	○ Fluent	
14	Image	Rules	 Enable 	 Disable 		
凹	Event	Image Size	 Auto-fill 	O 4:3	O 16:9	
	Storage	Auto Start Live View	⊖ Yes	No		
F0.	Vehicle Detection	Image Format	JPEG			
63	VCA	Encryption Key	•••••			
		Record File Settings				
		Record File Size	O 256M	• 512M	⊖ 1G	
		Save record files to	Charleman	Index of the		Browse
		Save downloaded files to	7 Designment Mathematical Inc.			Browse
		Picture and Clip Settings				
		Save snapshots in live view to	Charleman	and the second second		Browse
		Save snapshots when playback to		Index and the		Browse
		Save clips to		Indiffusion data		Browse
		Save clips to		and the second se		blowse

Click **Configuration** to enter configuration interface.

Figure 9-4 Configuration

9.6 Log

- 1. Go to Maintenance \rightarrow System \rightarrow Maintenance \rightarrow Log.
- 2. Set the search conditions.
- 3. Click Search.



Digital Video Recorder User Manual

Figure 9-5 Log

Chapter 10 Appendix

10.1 Glossary

Dual-Stream

Dual-stream is a technology used to record high resolution video locally while transmitting a lower resolution stream over the network. The two streams are generated by the DVR, with the main stream having a maximum resolution of 1080P and the sub-stream having a maximum resolution of CIF.

DVR

Acronym for Digital Video Recorder. A DVR is device that is able to accept video signals from analog cameras, compress the signal and store it on its hard drives.

HDD

Acronym for Hard Disk Drive. A storage medium which stores digitally encoded data on platters with magnetic surfaces.

DHCP

Dynamic Host Configuration Protocol (DHCP) is a network application protocol used by devices (DHCP clients) to obtain configuration information for operation in an Internet Protocol network.

HTTP

Acronym for Hypertext Transfer Protocol. A protocol to transfer hypertext request and information between servers and browsers over a network.

ΡΡΡοΕ

PPPoE, Point-to-Point Protocol over Ethernet, is a network protocol for encapsulating Point-to-Point Protocol (PPP) frames inside Ethernet frames. It is used mainly with ADSL services where individual users connect to the ADSL transceiver (modem) over Ethernet and in plain Metro Ethernet networks.

DDNS

Dynamic DNS is a method, protocol, or network service that provides the capability for a networked device, such as a router or computer system using the Internet Protocol Suite, to notify a domain name server to change, in real time (ad-hoc) the active DNS configuration of its configured hostnames, addresses or other information stored in DNS.

Hybrid DVR

A hybrid DVR is a combination of a DVR and NVR.

NTP

Acronym for Network Time Protocol. A protocol designed to synchronize the clocks of computers over a network.

NTSC

Acronym for National Television System Committee. NTSC is an analog television standard used in such countries as the United States and Japan. Each frame of an NTSC signal contains 525 scan lines at 60Hz.

NVR

Acronym for Network Video Recorder. An NVR can be a PC-based or embedded system used for centralized management and storage for IP cameras, IP Domes and other DVRs.

PAL

Acronym for Phase Alternating Line. PAL is also another video standard used in broadcast televisions systems in large parts of the world. PAL signal contains 625 scan lines at 50Hz.

PTZ

Acronym for Pan, Tilt, Zoom. PTZ cameras are motor driven systems that allow the camera to pan left and right, tilt up and down and zoom in and out.

USB

Acronym for Universal Serial Bus. USB is a plug-and-play serial bus standard to interface devices to a host computer.

