

APC Power-Saving Back-UPS ES 8 Outlet 700VA 230V CEE 7/7

BE700G-GR

Call for More Information +358 104466441



- Battery Backup & Surge Protector for Electronics and Computers
- Includes: CD with software, Telephone Cable, User Manual


Output	
Output power capacity	405Watts / 700VA
Max Configurable Power (Watts)	405Watts / 700VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	47 - 63 Hz
Output Frequency (not synced)	50Hz +/- 0.1% for 50Hz nominal
Topology	Standby
Waveform type	Stepped approximation to a sinewave
Output Connections	(4) Schuko CEE 7 (Surge Protection) (4) Schuko CEE 7 (Battery Backup)
Output Voltage Tolerance	+/- 5% static and 100% load step
Transfer Time	6ms typical : 10ms maximum

Input	
Nominal Input Voltage	230V
Input frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	Schuko CEE 7/7P
Cord Length	1.83meters
Input voltage range for main operations	180 - 266V
Maximum Input Current	10.0A

Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Batteries & Runtime	
Typical recharge time	16hour(s)
Replacement Battery	BE850G2-RS 
Expected Battery Life (years)	3 - 5
Battery Volt-Amp-Hour Capacity	86
Runtime	View Runtime Graph (Available in Technical Tab on site) View Runtime Chart (Available in Technical Tab on site)
Efficiency	View Efficiency Graph (Available in Technical Tab on site)

Communications & Management	
Interface Port(s)	USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators

Surge Protection and Filtering	
Surge energy rating	310Joules
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ-11 connector), Network line - 10/100 Base-T Ethernet (RJ-45 connector)
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical	
Maximum Height	89MM, 8.9CM
Maximum Width	224MM, 22.4CM
Maximum Depth	311MM, 31.1CM
Net Weight	6.93KG
Shipping weight	7.84KG
Shipping Height	127MM, 12.7CM
Shipping Width	279MM, 27.9CM
Shipping Depth	400MM, 40.0CM
Color	Black
Master Carton Dimensions (Length x Width x Height)	324MM
Master Carton Units	2.0

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Master Carton Weight	16.36
Pallet Dimensions	48inches
# of Layers per Pallet	4.0
# of Units per Layer per Pallet	20.0
Pallet Weight	1400.0lbs.
Units per Pallet	48.0
SCC Codes	1073130427170 0

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	40.0dBA

Conformance	
Approvals	CE
Equipment protection policy	Lifetime : 100000 Euro
Standard warranty	2 years repair or replace, 3 years repair or replace for European Union countries

Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains SVHCs
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.